

door catalogue
2024 1st edition

DOOR PROMOTION



*Sara ECO 2 doors with DRE aluminum door frames in aluminum and white colors are available from stock in selected configurations.

TABLE OF CONTENTS

FRAME CONSTRUCTION DOORS		Cassette tunnel cover PA	
Vetro E-Synchro	4	door frameless cassette B01	106
Sigma	6	DOORS WITH HIDDEN DOOR FRAME	
Estra	8 📵	Profi107	7-108
Torino	10	CADA ECO 2	
Verano	17) —		
Ena	NEV	······································	1 1 .
Triesta		FOLDING DOORS	
Solte		Folde	111
i e		•	
Reva		SIDE PANELS	
Fosca		Panel construction	114
Nestor		Frame construction	
Auri	22	,	
Elsa	24	TRANSOM LIGHTS AND SIDELIGHTS	
Premium	26	TRANSOM LIGHTS AND SIDELIGHTS	11
Piano		,	
Scala		INETRIOR ENTRANCE PANEL CONSTRU	CH
Verso		DOOR LEAVES	
Vetro A		Enter/Solid	118
•		SOLID RC2	
Vetro B		•	124
Vetro D		TECHNICAL DOOR LEAVES	
Lumio		Athos fire resistant doors . EI30	12
Vico	42	FORCA anti-burglary door leaves RC3, fire	12
FRAME CONSTRUCTION DOORS PAIL	NTED		40
		resistant	
Berge	44	Forca B RC3 anti-burglary door leaves	
Even	46	Olimp fire resistant doors. El30, El60	12
Nestor	48	Metal fire resistant door frame	13
Vetro E	50 NEV	Wooden fire resistant door frame	13
•		DOOR LEAVES WITH SOUND INSULATION	
PANEL CONSTRUCTION DOORS			
Nova -Cell	52	Enter Acoustic Rw=32dB	13
Wood	54	GLASS DOORS	
Claro	56		40
Grafi	58	Galla	
Lux	NF\		
Nova -Synchro		Glass doors technical informations	13
•		DOOR FRAMES	
Rivia			40
Galeria Alu		fixed rebated door frames	
Arte B		fixed non-rebated door frames	13
Carla	71	Adjustable door frames138	3-13
Finea and Finea B	72	Adjustable non-rebated door frames140)-14
Deco	74	Rebated adjustable door frames	
Modern		with variable heights	1/
•			т-т
Kanon		Adjustable non-rebated door frames	
Plus		with variable heights	
Standard		Adjustable door frames with inverted rebate	
Fano	84	Adjustable tunnel	14
Arte	86	Adjustable non-rebated door frames	
'		with architrave panels	14
PANEL DOORS PAINTED		Extension panels	
UNI	88 🚇		
Fargo	90	Metal fixed door frame	
BINITO		 , ,	15
·	_	adjustable metal door frame	
PANEL CONSTRUCTION DOORS CPL	LAMINATE	non-rebated	
Standard Invest	94 (II) NEV	Hybrid metal door frame	15
Standard CPL		Hybrid metal door frame	
•		non-rebated	15
PANEL DOORS WITH VARIABLE HEIG	HTS	Small angular steel frames	
Standard 10		,	
1		ACCESSORIES, ADDITIONAL INFORMAT	101
Modern		I .	
Plus	99 NE		
SLIDING SYSTEM		Decors	
SELD IN CONTRACTOR		graphic patterns in GRAFI collection	
			17
Wall mounted sliding system		Glass panes patterns	
Wall mounted sliding systemGlass doors sliding system		Architraves and skirting boards	
	102		176



VETRO E - natural halifax oak

EGGER 3 mm laminates 1st group

CLEAF 4 mm laminates 2nd group

















Horizontal cross-section of rebated VETRO E doors



Horizontal cross-section of non-rebated VETRO E doors



- » door leaf surface is coated with laminated, synchronous 3 mm or 4 mm thick board
- » reinforced MDF frame
- » core made of tubular chipboard
- » DECORMAT tempered laminated 8 mm glass pane with fixed width (regardless the width of the door leaf) or laminated black tempered 8 mm glass pane (opaque) with fixed width (regardless the door leaf width)

REBATED DOOR LEAF

- » straight edge in black Fig. 1
- » for natural halifax oak decor, the edge in the color of the door leaf or black
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (extra charge)

- » edge without rebate in black Fig. 2
- » for natural halifax oak decor, the edge in the color of the door leaf or black
- » sockets for 2 Estetic 80 recessed hinges in steel, black or white color (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

DOOR FRAMES

» for door leaves from the Vetro E collection in synchronous laminates, we recommend door frames in black matt foil 2 and in CPL laminate natural halifax oak in a longitudinal arrangement, in the second CPL price group

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » ventilation undercut
- » non-rebated door leaf

NOTE: third hinge Estetic 80 for non-rebated doors (extra charge is added to the price of the door frame)



SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: sliding VETRO E door leaves do not fit the sliding system with the PA door frame cassette.

NOTE: There is no possibility to shorten door leaf.

VETRO E – meets ventilation requirements for widths "80" - "100" with ventilation undercut

NOTE: It is required to use together with VETRO rebated door leaf model door frames equipped with 3 hinges.



VETRO E gray halifax oak



VETRO E natural halifax oak



VETRO E Halifax Tabac Oak



VETRO E white elm



VETRO E natural elm



VETRO E dark elm



SIGMA 4 - White

Laminated decor













- » stiles made of wood-based panels
- » 4mm flat HDF panel black lacquered high gloss

OPTIONS WITHOUT EXTRA CHARGE

» T2 ventilation sleeves

NON-REBATED OPENING DOOR LEAF

- » edge without rebate fig.1
- » sockets for two plate hinges (hinges constitute integral part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock
- » ash color non-rebated edge for white decor, non-rebated edge in the same color as door leaf color for other decors
- » alternatively, black non-rebated edge for all decors
- » hinges and locks colors: black, white, steel
- » door leaf in white decor or bleached craft oak is available with Finish foil door frame in the same decor as the door leaf, door leaf in other decors is available with black matt 2 decor door frame.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » door leaf "90" and "100"
- » ventilation undercut
- » cover strip for non-rebated double leaf door
- » double leaf door

door leaf price x2

» NOTE: third plate hinge for non-rebated doors (extra charge is added to the price of the door frame)



plate hinge







SIGMA 1



SIGMA 2



SIGMA 3



SIGMA 4



ESTRA 13 - cashmere matt

DRE-Cell Decor













3D Decor

















STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » 16mm flat panels
- » Estra 7-9 models have black glass pane frame and black muntin frame
- » Estra 10 model with a mirror
- » Estra 12-14 models have a glazing bar in the color of the door leaf

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane $\,$
- » holes for ventilation sleeves

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED OPENING DOOR LEAF (extra charge)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

DOOR LEAF WITH INVERETED REBATE (extra charge)

- » active single leaf door
- » straight edge fig 3

ESTRA 8

ESTRA 9

- » sockets for two recessed Estetic 1821 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

NOTE: This option is available only for matt foil decors


OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » door leaf with inverted rebate
- » cover strip for non-rebated double leaf door

» double leaf door door leaf price x2 NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is

added to the price of the door frame)
NOTE: It is required to use door frame equipped with 3 hinges together with rebated door leaf ESTRA.

* Note: Selected configurations of white matt rebated ESTRA 5 model are available in stock.



Panel in the same color as the door leaf

The side to which the door opens



edge with inverted rebate

ESTRA 11

ESTRA 12

ESTRA 13

ESTRA 10

MIRROR

ESTRA 14





TORINO 1 - bleached craft oak

Laminated decor



bleached craft oak





- » stiles made of wood-based panels
- $\!\!\!\!>$ 4 mm MAT DRE glass pane or 4 mm HDF flat panel in black lacquered gloss
- » flat panel in the same color as the door leaf

OPTIONS WITHOUT EXTRA CHARGE

» T2 ventilation sleeves REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in hinges
- » simple key lock, bathroom lock, cylinder lock or economic lock
- » edge in the same color as the door leaf
- » door leaves in white and bleached craft oak decors are available with the door frames covered with Finish foil in the same decor as the door leaf in the R-FINISH price group



OPTIONS AVAILABLE WITH EXTRA CHARGE

- » door leaf "90" and "100"
- » ventilation undercut
- » double leaf door

door leaf price x2



TORINO rebated door leaves must be used with 3 hinges door frames .



(4 panels in the same color as the door leaf)



(2 panels in the same color as the door leaf 2 glass panes or panels lacquered black)



TORINO 3 (4 glass panes or panels lacquered black)



TORINO 4
(1 panel in the same color as the door leaf 3 glass panes or panels lacquered black)



STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » double leaf door door leaf price x2
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: It is required to use door frame equipped with 3 hingestogether with VERANO rebated door leaf model









VERANO 0



VERANO 1



VERANO 2



VERANO 3



VERANO 4



VERANO 5

DRE-Cell Decor



STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane $\,$
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » double leaf door door leaf price x2
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge ${\it fig.~1}$
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- $\ensuremath{\text{\textit{»}}}$ sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: It is required to use door frames equipped with 3 hinges together with ENA rebated door leaf model .

















white matt

white

(textured)

white pine

siberian elm sand blea oak to

bleached oak textured

golden oak textured

lack matt 2



DRE-Cell Decor

*while stock last

grand oak

intage oal

elm

walnu america ebony*

light gray matt

evoke oak
Polish oak

3D Decor



STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane $\,$
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » double leaf door door leaf price x2
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

fixed edge fig. 2 edge without rebate

fig. 1

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: It is required to use door frame with 3 hinges together with TRIESTA rebated door leaf model. The left door is a mirror image of the right door.



TRIESTA 0



TRIESTA 1



TRIESTA 2



TRIESTA 3

DRE-Cell Decor





STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick (SOLTE 2 3)
- » flat panel insert (SOLTE 1 2)

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door » double leaf door
- door leaf price x2 » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

fig. 2 edge without rebate

fixed

fig. 1

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: Rebated "40" side panels available.

NOTE: It is required to use door frame equipped with 3 hinges together with SOLTE rebated door leaf model.



SOLTE panel - 4 mm thick







white white matt white pine (textured) *while stock last



















black matt 2






3D Decor



REVA 1 - white pine





STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » flat inserts (REVA 5-7)

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane $\,$
- » holes for ventilation sleeves

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: Rebated "40" side panels available.

NOTE: It is required to use door frame equipped with 3 hinges together with REVA rebated door leaf model.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » black VSG 22.1 safe, complex glass pane REVA 1 REVA 2


REVA 3.4

REVA 5

REVA 7

» double leaf door door leaf price x2

» NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)







FOSCA 0 - grand oak





- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » flat panel insert coated with silver laminate (FOSCA 1-3) or in door leaf colour (FOSCA 4-6)

OPTION WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » double leaf door

door leaf price x2

1 pc.

» NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING SYSTEM DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: There is possibility to make rebated "40" side panels.

NOTE: It is required to use door frame equipped with 3 hinges together with FOSCA rebated door leaf model.







A 1-3 FOSCA 4-6

FOSCA 1-3 (4mm HDF insert coated with silver laminate)

(4mm HDF insert coated in door leaf colour)



FOSCA 0 (5 glass panes)



FOSCA 1 (3 glass panes, 2 HDF panels)



FOSCA 2 (1 glass pane, 4 HDF panels)



FOSCA 3 (5 HDF panels)



FOSCA 4 (3 glass panes, 2 HDF panels)



FOSCA 5 (1 glass pane, 4 HDF panels)



FOSCA 6 (5 HDF panels)



NESTOR 1 - black matt 2

DRE-Cell Decor



















3D Decor



white pine

DOOR HANDLE WITH A BACKPLATE

The promotion applies to rebated and non-rebated door leaves from NESTOR collection in DRE-Cell Decor and 3D foil. Door handle model and finishing colors to choose from: WEGA, ATRIA, ARCTUS, POLARIS and ORION door handles and a backplate with a simple key or cylinder or a bathroom lock. The promotion lasts while stocks last.





STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » profiled 19mm MDF panels

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane $\,$
- » holes for ventilation sleeves

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

DOOR LEAF WITH INVERETED REBATE (extra charge)

- » active single leaf door
- » straight edge fig 3
- » sockets for two recessed Estetic 1821 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

NOTE: This option is available only for matt foil decors

OPTIONS AVAILABLE WITH EXTRA CHARGE


- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » door leaf with inverted rebate

added to the price of the door frame)

» cover strip for non-rebated double leaf door

» double leaf door door leaf price x2 NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is


NOTE: It is required to use together with NESTOR rebated door leaf model door frames equipped with 3 hinges.







AURI 8 - American walnut



- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » flat inserts (AURI 6-8)

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: Rebated "40" side panels available. It is required to use door frame equipped with 3 hinges together with AURI rebated door leaf model.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » black VSG 22.1 safe, complex glass pane AURI 0

AURI 1 **AURI 2, 5**

AURI 3

AURI 4

AURI 6


AURI 8

double leaf door

door leaf price x2

1 pc.

» NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)







ELSA A3 and ELSA 0 - sand oak

DRE-Cell Decor











3D Decor



DOOR HANDLE WITH A BACKPLATE

The promotion applies to rebated and non-rebated door leaves from ELSA collection in DRE-Cell Decor and 3D foil. Door handle model and finishing colors to choose from: WEGA, ATRIA, ARCTUS, POLARIS and ORION door handles and a backplate with a simple key or cylinder or a bathroom lock. The promotion lasts while stocks last.



- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » flat panel insert (ELSA A), profiled 19 mm MDF panels (ELSA B)

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- door leaf price x2 » double leaf door » NOTE: third Estetic 80 hinge for non-rebated doors (extra

ELSA collection is divided into A and B:

charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge **fig. 1**
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)


- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: Rebated "40" side panels available.

It is required to use door frame equipped with 3 hinges together with ELSA rebated door leaf model.









edge without rebate

1 pc.

cross-section of ELSA A

cross-section of ELSA B



ELSA A



ELSA A1



ELSA A2



ELSA A3



ELSA A4



ELSA B5



ELSA B6



ELSA B7



ELSA 0



ELSA B



Premium 4 - marrone chestnut structure





- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick

OPTION WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door

are used two glass panes.

door leaf price x2 » double leaf door » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING SYSTEM DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: There is possibility to make rebated "40" side panels.

NOTE: It is required to use door frame equipped with 3 hinges together with PREMIUM rebated door leaf model.



edge





PREMIUM 0-3

(4 mm glass pane)



In PREMIUM 12 and 13 models, from the top edge there

* PREMIUM 4-7, 12 (4 mm HDF inserts in door leaf colour)



1 pc.

** PREMIUM 8-11, 13 (4mm HDF inserts , coated with a silver laminate)



PREMIUM 0 PREMIUM 4* PREMIUM 8**



PREMIUM 1 PREMIUM 5* PREMIUM 9**



PREMIUM 2 PREMIUM 6* PREMIUM 10**



PREMIUM 3 PRFMIUM 7* PREMIUM 11**



PREMIUM 12 2 glass panes, 6 inserts in the colour of the door leaf



PREMIUM 13 2 glass panes, 6 inserts coated with a silver laminate



PIANO 0 - Polish oak 3D



STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » 16 mm convex panel (PIANO 1-2, PIANO 5-6) or 19 mm convex panel (PIANO 9-12)

OPTION WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane $\,$
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » double leaf door
 » NOTE: third Estetic 80 hinge for non-rebated doors (extra

charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING SYSTEM DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: There is possibility to make rebated "40" side panels.

It is required to use door frame equipped with 3 hinges together with PIANO rebated door leaf model.







panel PIANO 9-12







SCALA 0, SCALA B2 - white matt



DOOR HANDLE WITH A BACKPLATE

The promotion applies to rebated and non-rebated door leaves from SCALA collection in DRE-Cell Decor and 3D foil. Door handle model and finishing colors to choose from: WEGA, ATRIA, ARCTUS, POLARIS and ORION door handles and a backplate with a simple key or cylinder or a bathroom lock. The promotion lasts while stocks last.



- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » flat panel insert (SCALA A), 19 mm profiled MDF panels (SCALA B)

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- door leaf price x2 » double leaf door
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: Rebated "40" side panels available. It is required to use door frame equipped with 3 hinges together with SCALA rebated door leaf model.

SCALA collection is divided into A and B:

- A flat panel insert in door leaf colour
- B convex panel insert in door leaf colour











1 pc.

panel SCALA B, B1-B7













SCALA A5/B5









VERSO 0 - white pine

DRE-Cell Decor





- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm $\dot{}$ thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » double leaf door door leaf price x2

» NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF


- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock


SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles





1 pc.



VERSO 0









VERSO 4

^{*} Note: selected configurations of the VERSO model are available as stock orders, rebated in white matt.





VETRO A1 - dark wenge



NOTE: It is possible to order non-rebated door leaf in Dre-Cell white matt colour

corss-section of stile in non-rebated door leaf $\,$ $_{\text{A-milled edges}}$







VETRO collection glass panes have obverse and reverse sides (important in two door leaves opening inversely).

The below horizontal cross-sections show the arrangement of the glass pane in the obverse version. When selecting the reverse version, the glass pane is rotated $180^{\rm o}$ around the vertical axis.

Horizontal cross-section of door leaf VETRO A1-A4, A12-A15



Horizontal cross-section of door leaf VETRO A5, A10 - A11





- » reinforced MDF frame
- » core made of tubular chipboard
- » 8 mm tempered glass

OPTIONS WITHOUT EXTRA CHARGE

- » there is possibility to make ventilation undercut (A)
- » door leaf with revers positioning of glass pane
- » VETRO A1 four possible types of glass pane: DECORMAT, DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass

OPTIONS AVAILABLE WITH EXTRA CHARGE - AVAILABLE ONLY IN WHITE MATT DRE-CELL DECOR

- » non-rebated door leaf
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

ventilation undercut (A)



REBATED DOOR LEAF

- » R5 edge **fig. 1**
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (extra charge)

ONLY WHITE MATT

- » edge without rebate fig. 2
- $\ensuremath{\text{\textit{»}}}$ sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF


- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: Door leaf VETRO A in sliding version is not complementary product to sliding system hidden in the wall PA.

NOTE: There is no possibility to shorten door leaf.

NOTE: It is required to use door frame equipped with 3 hinges together with VETRO rebated door leaf model.

 $\mbox{V\-\sc E}\mbox{TRO}$ A - $\mbox{,}80\mbox{''-,}100\mbox{''}$ with ventilation undercut fulfill ventilation requirements.





VETRO A1



VETRO A2



VETRO A3



VETRO A4



VETRO A5



VETRO A10



VETRO A11



VETRO A12



VETRO A13



VETRO A14



VETRO A15





VETRO B14 - evoke oak



NOTE: It is possible to order non-rebated door leaf in Dre-Cell white matt colour

corss-section of stile in non-rebated door leaf A - milled edges







VETRO collection glass panes have obverse and reverse sides (important in two door leaves opening inversely).

The below horizontal cross-sections show the arrangement of the glass pane in the obverse version. When selecting the reverse version, the glass pane is rotated 180° around the vertical axis.

Horizontal cross-section of VETRO B1 - B4, B12 - B15









- » reinforced MDF frame
- » core made of tubular chipboard
- » 8 mm tempered glass

OPTIONS WITHOUT EXTRA CHARGE

- » there is possibility to make ventilation undercut (B)
- » VETRO B1 four possible types of glass pane: DECORMAT, DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass
- » door leaf with revers positioning of glass pane

OPTIONS AVAILABLE WITH EXTRA CHARGE - AVAILABLE ONLY IN WHITE MATT DRE-CELL DECOR

- » non-rebated door leaf
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

ventilation undercut (B)

VETRO B - doesn't fulfill ventilation requirements

REBATED DOOR LEAF

- » R5 edge **fig. 1**
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (extra charge)

ONLY WHITE MATT

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock


SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: Door leaf VETRO B in sliding version with "70" width is not complementary product to sliding system hidden in the wall PA.

NOTE: There is no possibility to shorten door leaf.

NOTE: It is required to use door frame equipped with 3 hinges together with VETRO rebated door leaf model. VETRO B - doesnt fulfill ventilation requirements.













VETRO B3



VETRO B4





VETRO B10



VETRO B11



VETRO B12



VETRO B13



VETRO B14



VETRO B15



VETRO D1 - anthracite elm



NOTE: It is possible to order non-rebated door leaf in Dre-Cell white matt colour


VETRO collection glass panes have obverse and reverse sides

(important in two door leaves opening inversely).

The below horizontal cross-section shows the arrangement of the glass pane in the obverse version. When selecting the reverse version, the glass pane is rotated 180° around the vertical axis.

corss-section of stile in non-rebated door leaf A-milled edges









- » reinforced MDF frame: narrow element with fixed width, wide element with variable width
- » core made of tubular chipboard
- » 8 mm tempered glass with fixed width, (regardless of the door leaf width)

OPTIONS WITHOUT EXTRA CHARGE

» door leaf with revers positioning of glass pane

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » ventilation undercut
- » black tempered laminated glass pane

REBATED DOOR LEAF

- » R5 edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (extra charge)

ONLY WHITE MATT

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock



edge R5



OPTIONS AVAILABLE WITH EXTRA CHARGE - AVAILABLE ONLY IN WHITE MAT DRE- CELL DECOR

- » non-rebated door leaf
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame) ventilation undercut



SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: Door leaf VETRO D in sliding version is not complementary product to sliding system hidden in the wall PA.

NOTE: There is no possibility to shorten door leaf.
VETRO D - widths "80" - "100" with ventilation undercut fulfill ventilation requirements.

NOTE: It is required to use door frame equipped with 3 hinges together with VETRO rebated door leaf model.



VETRO D1 glass pane transparent



VETRO D1 decormat



VETRO D1 decormat brown



VETRO D1 decormat graphite



LUMIO 1 - alpine white

FINISH decor













- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » flat inserts (LUMIO 7-9)

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves
- $^{
 m w}$ 4mm HDF flat panel gloss black lacquered in LUMIO 1, 7, 9 models instead of a glass pane

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lockNOTE: 3 hinges door frames should be used with LUMIO rebated door leaves .

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » black safety composite glass VSG 22.1
- LUMIO 1 LUMIO 2
- LUMIO 3, 6
- LUMIO 4
- LUMIO 5
- LUMIO 7
- LUMIO 9

double leaf door

door leaf price x2


1 pc.





* Note: Selected configurations of LUMIO 1 and LUMIO 9 models are available from stock, rebated in alpine white .







VICO 7 - riviera oak

FINISH decor













- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » flat inserts (VICO 5-7)

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves
- $\,$ » 4mm HDF flat panel gloss black lacquered in VICO 1, 5, 7 models instead of a glass pane

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lockNOTE: 3 hinges door frames should be used with rebated door leaves VICO.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » black safety composite glass pane VSG 22.1 VICO 1

VICO 2

VICO 3.4

VICO 5

VICO 7

» double leaf door

door leaf price x2

1 pc.

fig. 1







BERGE 6 - white

Painted decor



white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035

1 pc.

STANDARD OPTIONS

- » door leaf painted with acrylic UV varnish
- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » profiled 19mm MDF panels

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » double leaf door door leaf price x2
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

SLIDING DOOR LEAF

- » edge without rebate ${\it fig.\,2}$
- » socket for hook lock and/or for handles

NOTE: It is required to use door frame equipped with 3 hinges together with BERGE rebated door leaf model .





To ensure the highest quality of painted products, before painting process, both, door leaf and door frames are coated with special material which constitues solid base.





EVEN 0, 3 - white

Painted decor



white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035

1 pc.

STANDARD OPTIONS

- » door leaf painted with acrylic UV varnish
- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » cover strip for non-rebated double leaf door
- » double leaf door door leaf price x2
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: It is required to use door frame equipped with 3 hinges together with rebated door leaf.





To ensure the highest quality of painted products, before painting process, both, door leaf and door frames are coated with special material which constitues solid base.





NESTOR 12 - white

Painted decor



white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035



- » door leaf painted with acrylic UV varnish
- » stiles made of wood-based panels
- » glass pane MAT DRE 4 mm thick
- » profiled 19mm MDF panels

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane
- » holes for ventilation sleeves

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

DOOR LEAF WITH INVERETED REBATE (extra charge)


- » active single leaf door
- » straight edge fig 3
- » sockets for two recessed Estetic 1821 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

To ensure the highest quality of painted products, before painting porcess, both, door leaf and door frames are coated with special material which constitues solid base.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » plastic ventilation sleeves
- » non-rebated door leaf » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » door leaf with inverted rebate
- » cover strip for non-rebated double leaf door
- » double leaf door door leaf price x2 NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)


NOTE: It is required to use together with NESTOR rebated door leaf model door frames equipped with 3 hinges.





1 pc.

panel NESTOR






VETRO E - latte

Painted decor




white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035

Horizontal cross-section of rebated VETRO E doors



Horizontal cross-section of non-rebated VETRO E doors



- » door leaf painted with acrylic UV varnish
- » reinforced MDF frame: narrow element with fixed width, wide element with variable width
- » core made of tubular chipboard
- » DECORMAT tempered laminated 8 mm glass pane with fixed width (regardless the width of the door leaf) or laminated black tempered 8 mm glass pane (opaque) with fixed width (regardless the door leaf width)

REBATED DOOR LEAF

- » straight edge fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lockNON-REBATED DOOR LEAF (extra charge)
- » edge without rebate fig.1
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

NOTE: There is no possibility to shorten door leaf.

VETRO E - widths "80" - "100" with ventilation undercut fulfill ventilation requirements.

To ensure the highest quality of painted products, before painting process, both, door leaf and door frames are coated with special material which constitues solid base.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)
- » ventilation undercut
- » non-rebated door leaf



SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

NOTE: sliding VETRO E door leaves do not fit the sliding system with the PA door frame cassette.

NOTE: There is no possibility to shorten door leaf.

VETRO E - meets ventilation requirements for widths "80" - "100" with ventilation undercut

NOTE: It is required to use together with VETRO rebated door leaf model door frames equipped with 3 hinges.



VETRO E white (black glass pane)



ecru (black glass pane)



VETRO E latte (DECORMAT glass pane)



VETRO E ashen (DECORMAT glass pane)



NOVA 80 - sage oak, brushed gold inlay

Decor 1st group

















Decor 2nd group



Inlays







Possible model options: M1 - FULL DOOR LEAF, WITHOUT GLAZING

NOVA 20 - MDF bulaj NOVA 30 - STEEL BULAJ (AVAILABLE ONLY MAT OR

TRANSPARENT GLASS PANE) NOVA 40 - MDF frame in black matt 2 foil

NOVA 50 - 80 Vertical inlays made of laminate: brushed steel, brushed gold or moro matt

Steel BULAJ NOVA 30 - steel or black. Only matt or transparent glass pane available.



- » door leaf frame made of softwood
- » core made of "honeycomb'
- » glass pane MAT DRE 4 mm thick
- » the edge in the color of the door leaf or black
- » concrete oxide and antique copper decors available only with black edge

OPTIONS WITHOUT EXTRA CHARGE

- » ventilation sleeves
- » three hinges applies to rebated door leaf
- » DECORMAT BROWN, DECORMAT GRAPHITE glass pane and transparent glass

REBATED DOOR LEAF

- » straight edge fig. 1
- » 2 screw-in hinges in silver or black color
- » silver or black deadbolt lock with a simple key, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

DOOR LEAF WITH INVERETED REBATE (extra charge)

- » active single leaf door
- » straight edge fig 3
- » sockets for two recessed Estetic 1821 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock


» does not apply to door leaves with antique copper or oxide concrete decors

DOOR FRAMES

» for door leaves from NOVA collection it is recommended to use door frames in the same colour as door leaf or in black matt 2 decor

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent 37dB package (dropping seal + acoustic filling) NOVA 10, 50 - 80
- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90", "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » door leaf with inverted rebate
- » plastic ventilation grille
- » aluminum ventilation grille
- » there is possibility to purchase black or stainless steel BULAJ separately
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)



NOTE: the Silent package applies to rebated and non-rebated single leaf door.






WOOD M1 design W2 - dark oak

Decor









Model options with possibility to choose graphic patterns W1-W4:
M1 - full door leaf, without glazing
M2 - MDF bulaj in black matt decor
M3 - steel BULAJ in steel or black colour (only MATT or transparent glass pane available)
M4 - MDF frame in black matt decor





- » door leaf surface coated with the primer material, overprinted with the pattern and varnished
- » matt lacquer
- » door leaf frame made of MDF
- » stabilising insert honeycomb
- » glass pane MAT DRE 4 mm thick

NON-REBATED DOOR LEAF

- » edge without rebate in the colour of the door leaf
- » sockets for 2 recessed Estetic 80 hinges in steel, black or white color (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

DOOR FRAMES

» for the door leaves from the WOOD collection, we recommend to use lacquered frames made in the DRE-PRINT technology in the colour of door leaf unit

OPTION WITHOUT EXTRA CHARGE

- » holes for ventilation sleeves
- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » door leaf "100"
- » stabilising insert tubular chipboard
- » ventilation undercut
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)
- » aluminum ventilation grille



edge without rebate





CLARO M1

Decor









HIGH GLOSS LACQUER AS STANDARD

- » door leaf surface is coated with primer material and varnished
- » gloss varnish
- » door leaf frame made of MDF
- » core made of perforated chipboard
- » 4mm DRE MATT glass pane

MATT LACQUER AS STANDARD

- » door leaf surface is coated with primer material and varnished
- » matt lacquer
- » door leaf frame made of MDF
- » core made of "honeycomb"
- » 4mm DRE MATT glass pane

NON-REBATED DOOR LEAF

- » edge without rebate in white or black colour fig.1
- » sockets for 2 recessed Estetic 80 hinges in white, steel or black color (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

DOOR FRAMES

» for DRE-CLARO collection , we recommend to use white, black lacquered door frames made in DRE-PRINT technology, or door frames in black matt 2

OPTION WITHOUT EXTRA CHARGE

- » holes for ventilation sleeves
- » glass pane DECORMAT BROWN, DECORMAT GRAPHITE and transparent glass pane

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » door leaf "100"
- » ventilation undercut
- » stabilising insert tubular chipboard in matt lacquered door leaves

NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

» aluminum ventilation grille







white edgeband, white lock

black edgeband, black lock



Possible model options:

M1 - full door leaf, without glazing

M2 - MDF bulaj in black matt decor

M3 - steel bulaj (matt or transparent glass pane)

M4 - MDF frame in black matt decor

Steel BULAJ M3 - steel or black. Only matt or transparent glass pane available.



GRAFI M4-G2





STANDARD HIGH GLOSS LACQUERED DOOR LEAF

- » door leaf surface coated with the primer material, overprinted with the pattern and varnished (colour of the door leaf primed surface - white)
- » high gloss lacquer
- » door leaf frame made of MDF
- » core made of tubular chipboard
- » MAT DRE glass pane 4 mm thick (model M2, M4)

STANDARD MATT LACQUERED DOOR LEAF

- » door leaf surface coated with the primer material, overprinted with the pattern and varnished (colour of the door leaf primed surface - white)
- » matt lacquer
- » door leaf frame made of MDF
- » core made of "honeycomb"
- » MAT DRE glass pane 4 mm thick (model M2, M4)

NON-REBATED DOOR LEAF

- » edge without rebate in white or black colour fig.1
- » sockets for 2 recessed Estetic 80 hinges in white, steel or black color (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

DOOR FRAMES

» for GRAFI collection , we recommend to use white, black lacquered door frames made in DRE-PRINT technology, or door frames in black matt 2

OPTION WITHOUT EXTRA CHARGE

- » holes for ventilation sleeves
- » DECORMAT BROWN, DECORMAT GRAPHITE glass pane and transparent glass

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » door leaf "100"
- » ventilation undercut
- » stabilising insert tubular chipboard in matt lacquered door leaves

NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

» aluminum ventilation grille








white edgeband, white lock

black edgeband, black lock

Model options with possibility to choose graphic patterns G1-G25:









M1 - full door leaf, without glazing


M2 - MDF bulaj in black matt decor

M3 - steel BULAJ in steel or black colour (only MATT or transparent glass pane available)

M4 - MDF frame in black matt decor

Graphic patterns available on pages 60-61, 170-173.







GRAFI M1 G16











 $\ensuremath{^*}$ pattern versions available for the right and left door leaf



LUX 10 birch

Decor



















- » door leaf surface is coated with primer material in the colour of decor and varnished
- » high gloss lacquer
- » door leaf frame made of MDF
- » core made of perforated chipboard
- » MAT DRE glass pane 4 mm thick (model LUX 20, LUX 40)

NON-REBATED DOOR LEAF

- » edge without rebate in black colour fig.1
- » sockets for 2 recessed Estetic 80 hinges in black, white or steel color (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

DOOR FRAMES

for door leaves from LUX collection we recommend to use door frames lacquered in the same colour as the door leaf unit or in black matt decor 2

OPTION WITHOUT EXTRA CHARGE

- » holes for ventilation sleeves
- » DECORMAT BROWN, DECORMAT GRAPHITE glass pane and transparent glass

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » door leaf "100"
- » ventilation undercut
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)
- » aluminum ventilation grille



edge without rebate



black edgeband, black lock







LUX 20



LUX 30



LUX 40

Steel BULAJ LUX 30 - steel or black. Only matt or transparent glass pane available.



Nova 10 - natural halifax oak







- » door leaf surface is coated with laminated, synchronous 3 mm or 4 mm thick board
- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane MAT DRE 4 mm thick
- » edgeband in black colour
- » for natural halifax oak decor, the edge in the color of the door leaf or black
- » NOVA 50 80 Vertical inlays made of laminate: brushed steel, brushed gold or moro matt

OPTIONS WITHOUT EXTRA CHARGE

- » ventilation sleeves
- » three hinges applies to rebated door leaf
- » DECORMAT BROWN, DECORMAT GRAPHITE glass pane and transparent glass

REBATED DOOR LEAF

- » straight edge fig. 1
- » 2 screw-in hinges in silver or black color
- » silver or black deadbolt lock with a simple key, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

DOOR FRAMES

» for door leaves from NOVA collection, we recommend door frames in the DRE-CELL black matt 2 foil and in CPL natural halifax oak laminate for door leaves made in the natural halifax oak laminate, in a longitudinal arrangement in the second CPL price group

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent package 37dB (dropping gasket + acoustic insert) NOVA 10, 1st group Egger laminates
- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » "100" door leaves
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » there is possibility to purchase black or stainless steel BULAJ separately
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

NOTE: the Silent package applies to rebated and non-rebated single leaf door.

Steel BULAJ NOVA 30 - steel or black. Only matt or transparent glass pane available.



fixed edge





The option of combining the door frame in the DRE-Cell black matt 2 foil and natural halifax oak laminate








NOVA 20



NOVA 30



NOVA 40



NOVA 50



NOVA 60



NOVA 70



NOVA 80



**decor available only in horizontal graining

RIVIA 10 - marrone chestnut / black ST






3D Decor



grand oak





Rivia 20 black ST base



- » door leaf frame made of softwood
- » core made of tubular chipboard
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat uniform glass pane frame fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat uniform glass pane frame, rys. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate, flat uniform glass pane frame ${\bf fig.~2}$
- » socket for hook lock and/or for handles

RIVIA 80

NOTE: The door leaf is made in white matt or black ST with a choice of a center stripe decor. The edge of the door leaf is in the color of the central stripe. RIVIA 40 - BULAJ covered with white or black PVC foil, RIVIA 50 - BULAJ covered with silver foil. By default, the configurator selects the colour of the door frame in the same colour as the middle strip of the door leaf unit.

*** In RIVIA 70 and 120 models, the insert in the selected color has a vertical grain, except for the toffee oak color. In other models, the inserts have horizontal grain.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE, (applies to door leaf) **RIVIA 20, 30 RIVIA 40, 50**
- » white frost VSG 22.1 safe, complex glass pane **RIVIA 20, 30 RIVIA 40, 50**
- » non-rebated door leaf » door leaf width "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

fig. 1



edge



bar glazing flat unifo

fig. 2





edge without rebate

bar glazing flat uniform



RIVIA 90

RIVIA 100

RIVIA 110

RIVIA 120***

RIVIA 130



GALERIA ALU 20 - anthracite elm

DRE-Cell Decor white (textured) siberian elm white matt white pine silver 3D Decor Polish oak 3D grand oak CPL Laminate * white milky white ashen welsh oak



8mm inserts located in one plane with the door leaf surface on both sides

^{*} laminate available in models 10, 20, 30, 50, 60

^{**}while stock last

^{***} decor available only in horizontal wood grain





- » door leaf frame made of softwood
- » core made of tubular chipboard
- » edge with radius R 2,5 mm used in 0,15-0,20 mm CPL laminates
- » decorative inserts 8 mm
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock
- » straight edge or edge with radius R 2,5 mm made in directforming (in CPL laminate) fig 3

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate, flat glass pane frame fig. 2
- » socket for hook lock and/or for handles

Note: passive door leaf GALERIA ALU 20, 21, 22, 23, 24, 25, 60 without horizontal inserts in a uniform grain.

NOTE: the Silent package applies to rebated and non-rebated single leaf door.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent package 37dB (dropping seal + acoustic insert) GALERIA ALU 10 60 $\,$
- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE, (applies to door leaf)

GALERIA ALU 11, 13, 23

GALERIA ALU 21

GALERIA ALU 24, 25

GALERIA ALU 12, 22

» white frost VSG 22.1 safe, complex glass pane

GALERIA ALU 11

GALERIA ALU 13, 23

GALERIA ALU 21

GALERIA ALU 24

GALERIA ALU 25

GALERIA ALU 12

GALERIA ALU 22

- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door

» NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

leaf price x2







- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame ${\it fig.~1}$
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame , fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF


- » edge without rebate, flat glass pane frame fig. 2
- » socket for hook lock and/or for handles

OPTIONS AVAILABLE WITH EXTRA CHARGE

» glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to the door leaf) ARTE B 10, 20, 30 ARTE B 40, 50 ARTE B 60

» white frost VSG 22.1 safe, complex glass pane ARTE B 10, 20, 30 ARTE B 40, 50 ARTE B 60

- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door leaf price x2
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)









- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame, 19 mm MDF profiled panels fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame, 19 mm MDF profiled panels fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate, flat glass pane frame, 19 mm MDF profiled panels fig. 2
- » socket for hook lock and/or for handles

OPTIONS AVAILABLE WITH EXTRA CHARGE

» glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf)

CARLA 20 CARLA 30


CARLA 40

» white frost VSG 22.1 safe, complex glass pane CARLA 20

CARLA 30

CARLA 40

- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door leaf price x2 » NOTE: third Estetic 80 hinge for non-rebated doors (extra
- charge is added to the price of the door frame)







DRE-Cell Decor



FINEA 40 vintage oak



^{*}while stock last

*** decor available only in horizontal wood grain



- » door leaf frame made of softwood
- » core made of tubular chipboard
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)


- » edge without rebate, flat glass pane frame fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate, flat glass pane frame fig. 2
- » socket for hook lock and/or for handles

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf) FINEA 20, FINEA B 20 FINEA 30, 50, 60, FINEA B 30, 50, 60
- » white frost VSG 22.1 safe, complex glass pane FINEA 20, FINEA B 20 FINEA 30, FINEA B 30 FINEA 50, 60, FINEA B 50, 60
- » non-rebated door leaf
- » door leaf width "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » NOTE: third Estetic $8\bar{0}$ hinge for non-rebated doors (extra charge is added to the price of the door frame)





FINEA 10 FINEA B 10*



FINEA 20 FINEA B 20*



FINEA 30 FINEA B 30*




FINEA 40 FINEA B 40*



FINEA 50 FINEA B 50*



FINEA 60 FINEA B 60*





panels wood grain in FINEA



panels horizontal wood grain FINEA B



DECO 20 - concrete 2 with a black SLIM frame



^{***} decor available only in horizontal wood grain

^{*}while stock last









- » door leaf frame made of softwood
- » edge radius R 2.5 mm for CPL laminates 0.15-0.2 mm except for white, milky white, gray
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick
- » flat 4mm HDF panel in DECO 40

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame ${\bf Fig.~1}$ in the leaf decor or black Slim
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock
- » rounded glass pane frame, straight edge or edge with radius R 2,5 mm made in directforming (in CPL laminate)

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » non-rebated edge, flat glass pane frame ${\bf Fig.~2}$ in the leaf decor or black Slim
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock
- » edge without rebate, rounded glass pane frame (in CPL laminate) fig. 5

SLIDING DOOR LEAF


- » non-rebated edge and a choice of: flat glass pane frame in the leaf decor or black Slim, fig. 2 or a rounded glass pane frame fig.
 3
- » socket for hook lock and/or for handles
- » edge without rebate, rounded glass pane frame (in CPL laminate) fig. $5\,$

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » glass pane MAT DRE, DECORMAT BROWN , DECORMAT GRAPHITE (applies to door leaf) DECO 10, 20, 30
- » white frost VSG 22.1 safe, complex glass pane DECO 10, 20, 30
- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door

edge R 2.5 mm in CPL laminates except for white, milky white, gray

- » double leaf door leaf price x2
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)





DECO 10



DECO 20



R 2,5 edge

DECO 30



DECO 40



DECO 10 with black glass pane frame SLIM



DECO 20 with black glass pane frame SLIM



DECO 30 with black glass pane frame SLIM



DECO 40 with black glass pane frame SLIM



MODERN 20 - white matt

DRE-Cell Decor

3D Decor



*** decor available only in horizontal wood grain

*while stock last





- » door leaf frame made of softwood
- » core made of "honeycomb'
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame in the door leaf decor or black Slim, flat HDF panels, thickness 4 mm fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)


- » non-rebated edge, flat glass pane frame in the door leaf decor or black Slim, flat HDF panels, thickness 4 mm fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » non-rebated edge and a choice of: flat glass pane frame in the door leaf decor or black Slim, flat HDF panels, thickness 4 mm fig. 2 or a rounded glass pane frame, profiled MDF panels, thickness 19 mm fig. 3
- » socket for hook lock and/or for handles

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE, (applies to door leaf) MODERN 20
 - MODERN 30
 - MODERN 40
 - MODERN 50
- » white frost VSG 22.1 safe, complex glass pane
 - MODERN 20
 - MODERN 30
 - **MODERN 40**
 - MODERN 50
- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)





MODERN 10



MODERN 20



MODERN 30



MODERN 40



leaf price x2

MODERN 50



MODERN 10 with black glass pane frame SLIM



MODERN 20 with black glass pane frame SLIM



MODERN 30 with black glass pane frame SLIM



MODERN 40 with black glass pane frame SLIM



MODERN 50 with black glass pane frame SLIM



KANON 10 - American walnut, black glass pane frames





3D Decor

^{***} decor available only in horizontal wood grain

^{*}while stock last

- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame in the door leaf $\,$ decor or black Slim, flat HDF panels, thickness 4 mm fig. 1 $\,$
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)


- » non-rebated edge, flat glass pane frame in the door leaf decor or black Slim, flat HDF panels, thickness 4 mm fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » non-rebated edge and a choice of: flat glass pane frame in the door leaf decor or black Slim, flat HDF panels, thickness 4 mm fig. 2 or a rounded glass pane frame, profiled MDF panels, thickness 19 mm fig. 3
- » socket for hook lock and/or for handles

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE, (applies to door leaf) KANON 20 KANON 30 KANON 40
- » white frost VSG 22.1 safe, complex glass pane KANON 20 KANON 30 KANON 40
- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door
 » NOTE: third Estetic 80 hinge for non-rebated doors (extra
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)





KANON 10



KANON 20



KANON 30



KANON 40



KANON 10 with black glass pane frame SLIM



KANON 20 with black glass pane frame SLIM



KANON 30 with black glass pane frame SLIM



KANON 40 with black glass pane frame SLIM



PLUS 30 - white matt

DRE-Cell Decor



3D Decor

^{***} decor available only in horizontal wood grain

^{*}while stock last

- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » edge without rebate, flat glass pane frame, flat 4 mm HDF panels fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)


- » edge without rebate, flat glass pane frame, flat 4 mm HDF panels fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock


SLIDING DOOR LEAF

- » edge without rebate, flat 4 mm HDF panels and optional: flat glass pane frame, fig. 2 or rounded glass pane frame fig. 3
- » socket for hook lock and/or for handles

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf) PLUS 20 PLUS 40, 50, 60, 70, 80 PLUS 30
- » white frost VSG 22.1 safe, complex glass pane PLUS 20 PLUS 30 PLUS 40
- PLUS 70, 80 stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door leaf price x2
 » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)





PLUS 80

PLUS 70



STANDARD 10 - evoke oak





3D Decor

^{***} decor available only in horizontal wood grain

^{*}while stock last





- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock
- » Realization of orders in the investment standard after consultation with the Contracts Department. The investment standard is a door frame passage with a leaf open at an angle of $90^{\rm o}$ for interior doors: "80" 800 mm, "90" 900 mm.

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate and optional: flat glass pane frame fig.2 or rounded glass pane frame fig. 3
- » socket for hook lock and/or for handles

NOTE: the Silent package applies to rebated and non-rebated single


OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent package 37dB (dropping seal + acoustic insert) -STANDARD 10
- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf) STANDARD 20, 20s, 40, 40s, **BULAJ MDF**

STANDARD 50, 50s STANDARD 30, 30s STANDARD 60

» white frost VSG 22.1 safe, complex glass pane STANDARD 20, 20s, 40, 40s STANDARD 50, 50s, MDF BULAJ STANDARD 30, 30s STANDARD 60

- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90" and "100"
- » rebated door leaf "110" (only STANDARD 10)
- » additional upper single point mortise lock (available only in STANDARD 10 door leaf model with core made of perforated chipboard and fixed door frame)
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door door leaf price x 2 » there is possibility to purchase steel BULAJ separately
- in black or steel colour
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)



















STANDARD 20

STANDARD 20s

STANDARD 30

STANDARD 30s

STANDARD 40

STANDARD 40s



STANDARD 50



STANDARD 50s



STANDARD 60 **BULAJ MDF**





steel BULAJ



additional upper single point mortise lock (available only in STANDARD 10 door leaf model with core made of perforated chipboard and fixed door frame)





steel Bulai *

* only MATT or transparent glass pane available





FANO 10 - elm

DRE-Cell Decor

white (textured) white matt

white pine

siberian elm

silver

bleached oak textured light gray matt

vintage oak

3D Decor



*while stock last

- » door leaf frame made of softwood
- » core made of "honeycomb'
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame ${\it fig.\,1}$
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame, 19 mm MDF profiled panels fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate, rounded glass pane frame or flat glass pane frame, profiled 19 mm MDF panel fig. 3
- » socket for hook lock and/or for handles


OPTIONS AVAILABLE WITH EXTRA CHARGE

- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf) FANO 20, 20s FANO 30, 30s
- » white frost VSG 22.1 safe, complex glass pane FANO 20, 20s FANO 30, 30s
- » stabilising insert tubular chipboard
- » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door

» double leaf door

leaf price x2

» NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)













FANO 10

FANO 20s

FANO 30

FANO 30s



ARTE 40 - sand oak

DRE-Cell Decor

3D Decor



^{***} decor available only in horizontal wood grain

^{*}while stock last

leaf price x2

STANDARD OPTIONS

- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge, flat glass pane frame fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate, rounded glass pane frame or flat glass pane frame fig. 3
- » socket for hook lock and/or for handles

OPTIONS AVAILABLE WITH EXTRA CHARGE

» glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf) ARTE 10-30, 90 ARTE 40, 50

ARTE 80


» white frost VSG 22.1 safe, complex glass pane

ARTE 10, 20, 30 ARTE 40, 50

ARTE 80

ARTE 90

- » stabilising insert tubular chipboard » non-rebated door leaf
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)







UNI 10 - ashen

Decor



white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035



- » door leaf painted with acrylic UV varnish
- » door leaf frame made of MDF
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » third hinge to rebated door leaf

NOTE: To ensure highest quality of painted products, before painting process, both, door leaf and door frames are coated with special material which constitues solid base.

REBATED DOOR LEAF

- » straight edge fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles
- * Note: selected configurations of white rebated UNI 10 model are available from stock.


NOTE: the Silent package applies to rebated and non-rebated single leaf door.

DOOR LEAF WITH INVERETED REBATE (extra charge)

- » active single leaf door
- » straight edge fig 3
- » sockets for two recessed Estetic 1821 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent 37dB package (dropping seal + acoustic insert) UNI 10
- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf BULAJ MDF)
- » white frost VSG 22.1 safe, complex glass pane **BULAJ MDF**
- » stabilising insert tubular chipboard
- » core made of full chipboard
- » door leaf "90" and "100"
- » ventilation undercut
- » recuperative undercutting -15mm
- » non-rebated door leaf
- » door leaf with inverted rebate
- » cover strip for non-rebated double leaf door
- » plastic ventilation grille
- » aluminum ventilation grille
- » double leaf door
- leaf price x2 » there is possibility to purchase steel BULAJ separately
- in black or steel colour
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)















^{*} only MATT or transparent glass pane available



FARGO 10 - ashen

Decor



white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035



- » door leaf painted with acrylic UV varnish
- » door leaf frame made of MDF
- » core made of "honeycomb"

OPTIONS WITHOUT EXTRA CHARGE

- » ventilation sleeves
- » three hinges applies to rebated door leaf

NOTE: To ensure highest quality of painted products, before painting process, both, door leaf and door frames are coated with special material which constitues solid base.

REBATED DOOR LEAF

- » straight edge fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

SLIDING DOOR LEAF

- » edge without rebate fig. 2
- » socket for hook lock and/or for handles

DOOR LEAF WITH INVERETED REBATE (extra charge)

- » active single leaf door
- » straight edge fig 3
- » sockets for two recessed Estetic 1821 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock


OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent package 37dB (dropping seal + acoustic insert) FARGO 10 - 60
- » door leaf "90" and "100"
- » tubular chipboard
- » core made of full chipboard
- » ventilation undercut
- » recuperative undercutting -15mm
- » non-rebated door leaf
- » door leaf with inverted rebate
- » cover strip for non-rebated double leaf door
- » plastic ventilation grille
- » aluminum ventilation grille
- » double leaf door

leaf price x2

NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

NOTE: the Silent package applies to rebated and non-rebated single leaf door.








BINITO 20 white acrylic UV lacquer

Decor



white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035

DOOR HANDLE WITH A BACKPLATE

The promotion applies to rebated and non-rebated active door leaves from BINITO collection. Door handle model and finishing color to be choosen from: WEGA, ATRIA, ARCTUS and ORION door handles and a backplate with a simple key or a cylinder or a bathroom lock. The promotion lasts while stocks last.





types of milling in BINITO collection



- » door leaf painted with acrylic UV varnish » door leaf frame made of MDF
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

NOTE: To ensure highest quality of painted products, before painting process, both, door leaf and door frames are coated with special material which constitues solid base.

REBATED DOOR LEAF

- » straight edge, flat glass pane frame fig. 1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder insert lock or economic lock in steel, black or white color

SLIDING DOOR LEAF

- » edge without rebate, flat glass pane frame fig. 2
- » socket for hook lock and/or for handles

DOOR LEAF WITH INVERETED REBATE (extra charge)

- » active single leaf door
- » straight edge fig 3
- » sockets for two recessed Estetic 1821 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent package 37dB (dropping seal + acoustic insert) BINITO 10 - 90
- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE BINITO 11, 23 BINITO 21, 100
- » white frost VSG 22.1 safe, complex glass pane **BINITO 11**

BINITO 23

BINITO 21, 100


BINITO 24, 110

BINITO 24 BINITO 110

- » door leaf "90" and "100"
- » tubular chipboard
- » core made of full chipboard
- » non-rebated door leaf
- » ventilation undercut
- » recuperative undercutting -15mm
- » door leaf with inverted rebate
- » cover strip for non-rebated double leaf door
- » plastic ventilation grille
- » aluminum ventilation grille
- » double leaf door

leaf price x2

» NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)



NOTE: the Silent package applies to rebated and non-rebated single leaf door.





^{*} Note: selected configurations of the BINITO 20 model are available as stock orders, rebated in white matt.



BULAJ INVEST metal - honey oak











- » door leaf frame made of MDF
- » core made of "honeycomb"
- » transparent glass, thickness 4 mm

OPTIONS WITHOUT EXTRA CHARGE

- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge
- » edge with radius R 2.5 mm made by directforming available in CPL 2nd group Fig. 1 (rounded glass pane frame in CPL laminates)
- » straight edge fig. 2 (Slim glass pane frame in Finish foils)
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock
- » Realization of orders in the investment standard after consultation with the Contracts Department. The investment standard is a door frame passage with a leaf open at an angle of 90° for interior doors: "80" 800 mm, "90" 900 mm.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent package 37dB (dropping seal + acoustic insert) -STANDARD INVEST 10
- » glass pane MAT DRE (applies to door leaf) STANDARD INVEST 20, 70, 80, BULAJ MDF STANDARD INVEST 60
- » stabilising insert tubular chipboard
- » "100" door leaves
- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » there is possibility to purchase metal BULAJ separately in black or steel colour
- * Note: Selected configurations of rebated alpine white STANDARD INVEST 10 model are available from stock.







rounded







edge



glazing Slim









STANDARD INVEST 20



STANDARD INVEST 60



STANDARD INVEST 70



STANDARD INVEST 80



BULAJ INVEST MDF



steel BULAJ **INVEST**





steel Bulaj *



R 2,5 mm edge

* only MATT or transparent glass pane available



interior door leaves

- » edge radius R 2.5 mm only for laminates 0.15-0.20 mm from CPL 2nd group
- » straight edge for laminates 0.15-0.20 mm and 0.7 mm
- » door leaf frame made of softwood
- » core made of "honevcomb"
- » glass pane white bark 4 mm thick
- » CPL laminate 0.15 0.2mm or 0.7mm

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves
- » three hinges applies to rebated door leaf

REBATED DOOR LEAF

- » straight edge
- » edge with radius R 2.5 mm made by directforming available in 2nd group of CPL 0.15-0.20 mm laminates Fig. 1
- » straight edge for laminates 0.7 mm fig.1
- » 2 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock
- » Realization of orders in the investment standard after consultation with the Contracts Department. The investment standard is a door frame passage with a leaf open at an angle of $90^{\rm o}$ for doors: interior doors "80" 800 mm, "90" 900 mm.

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, rounded glass pane frame fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock

SLIDING DOOR LEAF

- » edge without rebate, rounded glass pane frame fig. 2
- » socket for hook lock and/or for handles


NOTE: colours equivalent: W0118 - WHITE

NOTE: the Silent package applies to rebated and non-rebated single leaf door.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent package 37dB (dropping seal + acoustic insert) -STANDARD 10 CPL
- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf) STANDARD 20, BULAJ MDF STANDARD 60
- » white frost VSG 22.1 safe, complex glass pane STANDARD 20 STANDARD 60
- » MDF BULAJ
- » stabilising insert tubular chipboard
- » "100" door leaves
- » door leaf "110" (only STANDARD 10) laminates 0.15 - 0.20 mm
- non-rebated door leaf
- » Additional upper single point mortise lock (available only in STANDARD 10 door leaf model with core made of tubular chipboard and fixed door frame)
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » ventilation undercut
- » recuperative undercutting -15mm
- » double leaf door
- » there is possibility to purchase steel BULAJ separately in black or steel colour
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

0.7 mm CPL laminate is also available in the "110" door leaf width and in Standard CPL 20, 60 models, BULAJ MDF, steel BULAJ - to place an order, please contact the Customer Service Department.









STANDARD 20



STANDARD 60



BULAJ MDF



steel BULAJ



leaf price x2

steel or black steel BULAJ (available only MAT or transparent glass pane)



R 2,5 mm edge























































REBATED AND NON-REBATED DO

STANDARD OPTIONS

- » door leaf frame made of softwood
- » core made of "honeycomb"

OPTIONS WITHOUT EXTRA CHARGE


» ventilation sleeves

REBATED DOOR LEAF

- » straight edge with the edging band
- » edge with radius R 2.5 mm made by directforming available in CPL 2nd group Fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lock



additional upper single point mortise lock (available only in STANDARD 10 door leaf model with core made of perforated chipboard and fixed door frame)

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » Silent 37dB package (1983) (dropping seal + acoustic filling) -STANDARD 10
- » Silent 37dB package (2110 and 2240) (dropping seal + acoustic filling) - STANDARD 10
- » core made of: perforated chipboard (1983) tubular chipboard (2110 and 2240)
- » door leaf "90" "100" (1983) DRE CELL » door leaf "90" "100" (2110 and 2240) DRE CELL » door leaf "90" "100" (1983) DRE CELL
- » door leaf "100" (2110 and 2240) DRE CPL
- » non-rebated door leaf
- » ventilation undercut
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door
- leaf price x2 » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

There is available 0,7 mm CPL laminate- to place an order and for more information please contact Customer Service Department.

Door leaf, dependent on selected height option - 1983 mm, 2110 mm or 2240 mm is dedicated to door frames with three hinges in corresponding heights.

NOTE: colours equivalent: W0118 - WHITE



R 2,5 mm edge in CPL laminate



198 STANDARD 10



standard height



211 STANDARD 10



224 STANDARD 10





- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves

REBATED DOOR LEAF

- » straight edge, flat glass pane frame (in CPL laminate rounded $\,$ glass frame pane) flat 4 mm HDF panels fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame (in CPL rounded glass pane frame), flat 4 mm HDF panels fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lockNOTE: colours equivalent: W0118 - WHITE

NOTE: In rebated door leaves with CPL laminates there is possibility to choose a door leaf with an edge radius R=2.5 mm, except for white, milky white and gray laminates.

NOTE: Different heights are available in all models of MODERN

Door leaf, dependent on selected height option - 1983 mm, 2110 mm or 2240 mm is dedicated to door frames with three hinges in corresponding heights.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf) MODERN 20 MODERN 30 MODERN 40 MODERN 50
- » white frost VSG 22.1 safe, complex glass pane p. 77
- » core made of: perforated chipboard (1983 and 2043) tubular chipboard (2110 and 2240)
- » door leaf "90" and "100" (1983 and 2043)
- » door leaf "90" and "100" (2110 and 2240)
- » non-rebated door leaf
- » ventilation undercut
- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- leaf price x2 » double leaf door
- » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

NOTE: collection MODERN 10-50 coated with CPL laminate in standard height is available i sliding version.





edge





rounded glass

pane frame (CPL)





without rebate





rounded glass pane frame (CPL)



198 MODERN 30



standard height



211 MODERN 30



224 MODERN 30



CPL laminate 1st group



white pine

white matt

white







siberian



silver




sand



vintage oa









decor available while supplies last













- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane white bark 4 mm thick

OPTIONS WITHOUT EXTRA CHARGE

- » glass pane "chinchila" or "window blind"
- » ventilation sleeves

REBATED DOOR LEAF

- » straight edge, flat glass pane frame (in CPL laminate rounded $\,$ glass frame pane) flat 4 mm HDF panels fig. 1
- » 3 silver screw-in pivot hinges
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock

NON-REBATED DOOR LEAF (EXTRA CHARGE)

- » edge without rebate, flat glass pane frame (in CPL laminate rounded glass pane frame), flat 4mm HDF panels fig. 2
- » sockets for 2 recessed Estetic 80 hinges (hinges constitute a part of the door frame)
- » magnetic simple key lock, bathroom lock, cylinder lock or economic lockNOTE: colours equivalent: W0118 - WHITE NOTE: In rebated door leaves with CPL laminates there is

possibility to choose a door leaf with an edge radius R=2.5 mm, except for white, milky white and gray laminates.

NOTE: Different heights are available in all models of PLUS

Door leaf, dependent on selected height option - 1983 mm, 2110 mm or 2240 mm is dedicated to door frames with three hinges in corresponding heights.

OPTIONS AVAILABLE WITH EXTRA CHARGE

» glass pane MAT DRE, DECORMAT BROWN, DECORMAT GRAPHITE (applies to door leaf) PLUS 20 PLUS 40, 50, 60, 70, 80


PLUS 30

- » white frost VSG 22.1 safe, complex glass pane p. 81
- » core made of: perforated chipboard (1983 and 2043) tubular chipboard (2110 and 2240)
- » door leaf "90" and "100" (1983 and 2043) » door leaf "90" and "100" (2110 and 2240)
- » non-rebated door leaf
- » ventilation undercut

flat

- » plastic ventilation grille
- » aluminum ventilation grille
- » cover strip for non-rebated double leaf door
- » double leaf door
- leaf price x2 » NOTE: third Estetic 80 hinge for non-rebated doors (extra charge is added to the price of the door frame)

NOTE: collection PLUS 10-80 coated with CPL laminate in standard height is available in sliding version.



frame (CPL)







ENA - white matt

The DRE wall-mounted sliding system is designed for single-leaf or double-leaf interior doors, in the sliding variant. It can be used for doors in our offer, with the following finishes: DRE-Cell, 3D foil, CPL laminates, as well as painted doors, except for the collections: Enter, Enter Akustik, Solid, Solid RC2, Forca B, fire resistant doors, glass doors and doors with variable heights.

In our sale offer there are available two different types of sliding system:

NS - system mounted directly on the wall

NT - sliding system mounted together with adjustable tunnel

There are two options of NT sliding system:

- » mounted together with adjustable tunnel with 63 mm architrave
- » mounted together with adjustable tunnel with 80 mm architrave

Set of sliding system comprises of: sliding guide bar with hardware (LEON SN 150, 180, 200), spacing board, masking strip, and fender beam (fender beam is available for single leaf - for doors with hook lock option in fender beam there is milling for latch).

The NT system is additionally supplemented with two 16 mm thick spacer strips with cross-sections adapted to the width of the architraves of 63 mm or 80 mm. The NS and NT systems also differ in the cross-section of the masking strip.

To complete entire set of sliding doors it is necessary to purchase sliding leaf unit in following dimensions:

Single leaf door: "60", "70", "80", "90", "100" Double leaf door: "2x60", "2x70", "2x80", "2x90", "2x100"

Door leaf might be equipped with sockets for lock and/or handle - those accessories must be purchased separately.

In the system mounted with adjustable tunnel NT, it is necessary to purchase adjustable tunnel separately.


CPL 2nd group laminate applies to the natural halifax oak laminate with horizontal graining.



ACCESSORIES

- » round handle 1 pcs.
- » oval handle 1 pcs.
- » Hook lock with the key with two round or oval handles
- » hook lock with toilet option with two round or oval handles
- » hook lock with cylinder lock insert with two round handles
- » One set of door handle for single leaf door consist of 2 pcs.

masking strip with guide bar



Masking strip and guide bar for double sliding system is made by connecting two elements of single system.



hook lock with a key and a handle round

on a tunnel with an architrave 63 mm on a tunnel with an architrave 80 mm



NT - vertical cross-section


ock hook lock with ey and key and dle handle ad oval handle

Single sliding system


Dimension	Masking strip		Guide bar
door [mm]	Mz Mw		Pa
644, 744	1620	1588	1500
844	1920	1888	1800
944	2120	2088	2000
1044	2160	2128	2000

double leaf door sliding system


Dimension	Maskir	Guide bar	
door [mm]	Mz	Mw	Pa
2 x 644	2 x 1519	2 x 1503	2 x 1500
2 x 744	2 x 1519	2 x 1503	2 x 1500
2 x 844	2 x 1819	2 x 1803	2 x 1800
2 x 944	2 x 2019	2 x 2003	2 x 2000
2 x 1044	2 x 2063	2 x 2047	2 x 2000



NS - vertical cross-section



NT - vertical cross-section



Single sliding system

symbol	"60"	"70"	"80"	"90"	"100"
Α	602	702	802	902	1002
С	646	746	846	946	1046
D	664	764	864	964	1064
Е	752	852	952	1052	1152
E*	786	886	986	1086	1186
S	644	744	844	944	1044


double leaf door sliding system

symbol	"120"	"140"	"160"	"180"	"200"
Α	1200	1400	1600	1800	2000
С	1244	1444	1644	1844	2044
D	1264	1464	1664	1864	2064
Е	1350	1550	1750	1950	2150
E*	1384	1584	1784	1984	2184
S**	644	744	844	944	1044


E* refers to a tunnel with an architrave. T80

Height of sliding door leaf unit - 2043 mm total height of sliding system - 2154 mm

NS - horizontal cross-section (left system)



NT - horozontal cross-section (left system) $|\frac{E}{D}$



^{*} is not available in double leaf system

NOTE: In double sliding system masking strip is connected on lenght, by two single elements.

S** width of single leaf door





The "Spazio" sliding system for glass doors - made of anodized aluminum, is a complete solution designed for ready-made door frames. The set includes a running rail with a straight or oval blind, as well as elements for hanging the sliding glass pane and a bottom door guide. There are two options of Spazio System (only difference is in the shape of external blende):

- » Spazio TP with straight blende
- » Spazio TO with oval blende

PRICE

» price of sliding system for a glass doors

To complete the whole system it is reccomended to buy glass door leaf in sliding version from Galla collection. There is designed for this solution round handle.

OPTIONS AVAILABLE WITH EXTRA CHARGE

» door handle (two-sided)




(stainless steel)

sliding glass door leaf

Note: There is no possibility to make ventilation option.

Prices of GALLA glass door leaves on page 133



A - A vertical crosssection of Spazio TP

A - A vertical crosssection of Spazio TO

A - A vertical crosssection of Spazio TO

58,6

58,6

60

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

7112

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

9002

90

Tab. Dimensions S Р Α "60" 630 590 1340 "70" 730 690 1540 1740 "80" 830 790 "90" 930 890 1940

- S width of door leaf unit
- A width of wall passage
- P lenght of guide channel

SLIDING SYSTEM SPAZIO CD MOUNTED ON-WALL SLIDING SYSTEM DOOR LEAF





Wall-mounted sliding system with an anodized guide and rectangular blende. Designed for panel and frame construction doors. This solution is intended for finished door frames.

To complete the system, you must purchase a sliding door from our offer in a version with a handle. The holder must be purchased separately (information on page 101).


WHOLE SET COMPRISES OF:

- » guide channel with side caps
- » system sliding trolleys
- » door leaf hangers
- » bottom stopper
- » assembly kit (screws and bolts)





vertical cross-section



- A width of wall passage S - width of door leaf unit
- L lenght of guide channel

	Α	S	L
"60"	600	644	1370
"70"	700	744	1570
"80"	800	844	1770
"90"	900	944	1970
"100"	1000	1044	2170



Sliding system doors hidden in the wall (pocket system) PA - STANDARD 10 vintage oak






3D Decor



*** decor available only in horizontal wood grain

*while stock last

Painted decor



white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035

PA DOOR FRAME CASSETTE

System assembly involves embedding the cassette in the construction of profiles used to build a plasterboard wall (or other construction) with a thickness of:

- » 100 mm for the PA 100 mm door frame cassette
- » 125 mm for the PA 125 mm door frame cassette


Next, wide surfaces construction with the usage of 12.5mm plasterboards (plasterboards must be purchased separately) and finishing these surfaces and assembly of Tunnel Cassette Cover.

NOTE: VETRO A, VETRO D and VETRO B door leaf with a width of "70" do not fit the 100 mm and 125 mm PA cassettes.

In addition, the 100 mm PA cassettes cannot be used with door leaves with locks and panel construction doors with glazing or panels

THE SET INCLUDES:

- » cassette elements made of aluminum elements and accessories for its assembly $\,$
- » elements that allow for decorative built-up jambs so called Tunnel Cassette Cover with the architraves



DOOR FRAMELESS CASSETTE B01

SLIDING SYSTEM DOOR LEAF interior door leaves

DOOR FRAMELESS CASSETTE B01


Door frameless cassette with the possibility of assembly and disassembly of the door leaf after cassette assembly and finishing . System assembly involves embedding the cassette in the construction of profiles used to build a plasterboard wall (or other construction) with a thickness of:

- » 100 mm for the B01 100 mm door frameless cassette
- » 125 mm for the B01 125 mm door frameless cassette

Then covering wide surfaces with 12.5 mm plasterboards (plasterboards must be purchased separately) and finishing these surfaces.

LIST OF DOOR COLLECTIONS AND MODELS AVAILABLE IN THE DOOR FRAMELESS CASSETTE SYSTEM B01:

ESTRA; VERANO; ENA; TRIESTA; SOLTE; REVA; FOSCA; NESTOR; AURI; ELSA; PREMIUM; PIANO; SCALA; VERSO; BERGE; EVEN; NOVA 10; RIVIA 10, RIVIA 60-130; GALERIA ALU 10, 20, 30, 50, 60; FINEA 10, 40; STANDARD 10, UNI 10; FARGO 10-60; BINITO 10-90 The door leaves have additional milling on the upper edge. Doors with locks and panel constructions doors with glazing and panels cannot be used with B01 door frameless cassettes.



Width	S	А	С	D	G
60	644	626	1360	1380	659
70	744	726	1560	1580	759
80	844	826	1760	1780	859
90	944	926	1960	1980	959
100	1044	1026	2160	2180	1059

- * variant of B01 cassette for 125 mm wall
- ** variant of B01 cassette for 100 mm wall
- *** wall elements are not components of the product
- S door leaf width
- A width of the door frame passage
- C total width of cassette
- D width of walls passage prepared for cassette
- G depth of ready cassette





NON-REBATED - OPENED OUTWARDS AND INVERTED REBATE - OPENED INWARDS

The PROFI system door with an aluminum door frame and a 50 mm thick door leaf is an innovative solution that allows for creative interior design with the usage of invisible doors, with the option of finishing the door leaf surface in the same colors as the walls.

PROFI DOOR STRUCTURE INCLUDES:

Aluminum door frame, invisible after installation, built into the reveal or covered with plasterboards. After masonry processing, only the frame notch is visible, ready for painting, e.g. in the color of the walls.

Non-rebated panel construction door leaf and inverted rebate in two finishing options:

- » Wide door leaf surfaces primed and ready for painting or wallpapering (e.g. in the color of the walls). The edges of the door leaf are covered with a edging that can be painted. Painting should be done on your own or you can choose a painted decor.
- » Wide surfaces of the door leaf and edges painted with white acrylic UV varnish.

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » ventilation undercut
- » dropping seal
- » Silent package 37dB (dropping seal + acoustic insert) Standard 2043
- » Silent package 37dB (dropping seal + acoustic insert) Standard 2240

Non-rebated door frame profile



Inverted door frame profile rebates



Door leaf decors:

primed

Decor

Painted decor




white acrylic UV varnish - RAL 9003


Extra charge for the third Estetic 80 hinge



NON-REBATED - OPENED OUTWARDS IN THE 2043, 2240 STANDARD NORMS

Cross-section of the 50mm non-rebated door - opened outwards





Profi door width dimensions


	S	Α	С	D
"60"	600	586	690	700
"70"	700	686	790	800
"80"	800	786	890	900
"90"	900	886	990	1000
"100"	1000	986	1090	1100

Dimensions of non-rebated door leaves

Difference of their reputed deer leaves						
standard	Н	HŚ	hw	H0		
2043	2043	2044	2096	2101		
2240	2240	2241	2293	2298		

INVERTED REBATE - OPENED INWARDS IN THE 2043, 2240 STANDARD NORMS

Cross-section of 50mm inverted rebate door - opened inwards




Profi door width dimensions

	S	Α	С	D
"60"	600	586	690	700
"70"	700	686	790	800
"80"	800	786	890	900
"90"	900	886	990	1000
"100"	1000	986	1090	1100

height dimensions of rehated doors

neight dimensions of repated doors						
standard	Н	HŚ	hw	H0		
2043	2053	2054	2106	2111		
2240	2250	2251	2303	2308		

Vertical section of 50mm inverted rebate door - opened inwards



- S door leaf width
 A width of passage in door frame unit
 C external width of door frame
 D required width of wall opening
 HO height of the wall opening



Door leaf decors

DRE-Cell

Decor

1st group

DRE-Cell



- * decor with a door leaf edge in black colour
- **while stock last
- *** decor available only in horizontal wood grain





Painted decor white ashen latte ecru

white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035

CPL Laminate



Decor

Available colours of aluminum door frames



aluminum



White RAL 9003



black





NON-REBATED - OPENED OUTWARDS AND INVERTED REBATE - OPENED INWARDS

Sara Eco 2 door leaf is an innovative solution for creative interior design with the use of "invisible" doors. This unique construction gives possibility to finish surface of door leaf in the colors of the walls.

CONSTRUCTION OF SARA ECO 2 DOOR LEAF COMPRISES OF:

Aluminum door frame, invisible after installation, built into the reveal or covered with plasterboards. After masonry processing, only the frame notch is visible, ready for painting, e.g. in the color of the walls.

Non-rebated panel construction door leaf and inverted rebate in two finishing options:

- » Wide door leaf surfaces primed and ready for painting or wallpapering (e.g. in the color of the walls). The edges of the door leaf are covered with a edging that can be painted. Painting should be done on your own or you can choose painted decors.
- » Wide door leaf surfaces covered with foils from DRE-Cell, 3D, CP black ST groups or with painting foil in the group of painted decors, the edges of the door leaf covered with the edging in the color of the foil (except for antique copper and concrete oxide colors).

OPTIONS AVAILABLE WITH EXTRA CHARGE WITH PRIMER

- » ventilation undercut
- » recuperative undercutting -15mm
- » tubular chipboard in standard 202
- » tubular chipboard in 220 standard
- » tubular chipboard in standard 240

STANDARD OPTION

- » door leaf frame made of softwood
- » sockets for 2 or 3 recessed hinges, new hinges with increased load capacity up to 60 kg are used in white and black door frame colors
- » core made of "honeycomb"
- » white or silver simple key magnetic lock, toilet lock, cylinder lock or economic lock

OPTIONS AVAILABLE WITH EXTRA CHARGE IN DRE-CELL, 3D AND PAINTED

- » ventilation undercut
- » recuperative undercutting -15mm
- » plastic ventilation grille
- » aluminum ventilation grille
- » dropping seal
- » tubular chipboard in standard 202
- » tubular chipboard in 220 standard
- » tubular chipboard in standard 240

Price of the door frame includes 2 or 3 hidden concealed hinges. Note: in option with stabilising insert as tubular chipboar, in standard 202 it is required to use 3 hinges.







DRE ALUMINUM DOOR FRAME NON-REBATED DOOR LEAVES AND INVERTED REBATE

NON-REBATED - OUTWARD OPENING, DRE DOOR FRAME

Horizontal cross-section of the Sara Eco 2 non-rebated door - opening outwards



Vertical cross-section of the Sara Eco 2 nonrebated door leaves - opening outwards




Dimensions of the door leaf width Sara height dimensions of rebated doors

				Eco 2
	S	Α	С	D
"60"	620	605	690	700
"70"	720	705	790	800
"80"	820	805	890	900
"90"	920	905	990	1000
"100"	1020	1005	1090	1100


standard	Н	HŚ	hw	H0			
202x	2020	2020	2062	2070			
220X	2200	2200	2242	2250			
240X	2400	2400	2442	2450			

INVERTED REBATE - INWARD OPENING, DRE DOOR FRAME

Cross-section of Sara Eco 2 with inverted rebate - opened inwards



Vertical section of Sara Eco 2 with inverted rebate - opened inwards



Dimensions of the door leaf width Sara Eco 2

Difficisions of the door leaf width 3								
	S	Α	С	D				
"60"	620	605	690	700				
"70"	720	705	790	800				
"80"	820	805	890	900				
"90"	920	905	990	1000				
"100"	1020	1005	1090	1100				

- S door leaf width
- A width of passage in door frame unit C external width of door frame D required width of wall opening

height dimensions of rehated doors

rieignit dimensions of repated doors							
standard	H*	Hś *	Hw*	H0 *			
202x	2030	2030	2072	2080			
220X	2210	2210	2252	2260			
240X	2410	2410	2452	2460			



folding doors FOLDE 10 - white matt





3D Decor

*** decor available only in horizontal wood grain

*while stock last



FOLDING DOORS FOLDE interior door leaves

The folding door system is characterized by the fact that when opening the door, the leaves fold into a position parallel to each other. The folding door system includes:

- » two-elements door leaf connected by 3 hidden recessed hinges
- » adjustable door frame for folding doors

STANDARD OPTIONS


- » door leaf frame made of softwood
- » core made of "honeycomb"
- » straight edge fig. 1
- » single-point mortise simple key lock, bathroom lock, cylinder lock or economic lock
- » 3 hidden recessed ISTAR hinges installed between twoelements of door leaf unit

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » core made of tubular chipboard
- » door leaf "90" and "100"



Cross-section of folding doors in closed position* (right doors, left doors are mirror reflection)




Tab. Dimensions

	S	Α	В	С	D	Е
"80"	844	806	830	850	880	990
"90"	944	906	930	950	980	1090
"100"	1044	1006	1030	1050	1080	1190


D - required width of wall opening

NOTE: There is no possibility to shorten door leaf.



*NOTE: When doors are fully opened, the door fittings slightly reduce the clear opening by approx. 10 cm. (this value doesn't take into account door handle)

vertical cross-section



PANEL CONSTRUCTION







STANDARD OPTIONS

- » door leaf frame made of softwood
- » core made of "honeycomb"
- » glass pane 4 mm thick: white bark, "window blind", CHINCHILA, MAT DRE, DECORMAT BROWN or DECORMAT GRAPHITE.
- » 2 silver screw-in pivot hinges
- » latch strike plate and two flush bolts
- » options: straight edge * , flat glass pane frame or black Slim glass pane frame fig. 1

OPTION WITHOUT EXTRA CHARGE

- » three hinges applies to rebated door leaf
- » black glass pane frame Slim

OPTIONS AVAILABLE WITH EXTRA CHARGE

» white frost VSG 22.1 safe, complex glass pane DOSTAWKA 30 EXTRA 40

ADDITIONAL BOX 41

core made of tubular chipboard

//,

» door frame for door leaf with side panel

+30%

Side panel it is passive rebated door leaf unit with "40" width and 40 mm thick, with glazing or without glazing option, in uniform wood grain. Side panels can be paired with interior rebated door leaf in the following combination: "60+40"; "70+40"; "80+40"; "90+40"; "100+40".

Side extension 10 can be used for rebated interior doors. Side extension 30 is suitable for ARTE 10-30 models and STANDARD 30. Side extension 40 is suitable for ARTE 40, 50, 90 models; STANDARD 40, KANON 30, DECO collection. Side extension 41 is adapted to MODERN 30 and PLUS 30 models.

To make the best possible match of side panel to door leaf unit, besides selection of model, it is necessary to choose the correct colour, type of the edge and number of hinges.

NOTE: There is no possibility to shorten side panels.







^{***} decor available only in horizontal wood grain

^{*}while stock last



FRAME CONSTRUCTION

STANDARD OPTIONS

- » stiles made of wood-based panels
- » glass pane 4 mm: MAT DRE, decormat brown, decormat graphite or transparent glass
- » 3 silver screw-in pivot hinges
- » latch strike plate and two flush bolts
- » straight edge ${\it fig.~1}$

OPTIONS AVAILABLE WITH EXTRA CHARGE

» door frame for door leaf with side panel

+30%

fig. 1

NOTE: Price of side panel is equal to the price of corresponding door leaf model.

There is possibility to make side panels to all frame construction door leaf.

available in presented collections, in following combinations: "60+40"; "70+40"; "80+40"; "90+40"; "100+40"

NOTE: There is no possibility to shorten side panels.






*while stock last

TRANSOM LIGHTS / SIDELIGHTS





Possible configuration of transom lights/side lights



TRANSOM LIGHTS AND SIDELIGHTS

Transom lights / sidelights are non-openable, glazed partitions between rooms, which can be an independent structure or a complement to interior doors (except for glass doors) with a fixed door frame. Transom lights /sidelights are manufactured and delivered as a set of elements to be assembled. The set includes:

- » two horizontal and two vertical main beams
- » set of cover and instalation strips
- » set of gaskets
- » main beam couplers

Transom lights/sidelights are used in interior doors with a fixed door frames and they come in the following decors DRE-Cell, 3D, CPL laminate 0,15-0,20 mm and painted.

NOTE: The offered product does not include the glass pane, it must be purchased separately. We recommend using 4 mm thick tempered glass pane. The installation of transom lights / sidelights should be carried out after the completion of "wet" construction works.





Fig. A cross-section of the transom light/sidelights



Dimensions of transom lights/sidelights

height total	width total	lenght of the perimeter
2073 mm	Z	2*2073+2*Z
N	Z	2*N+2*Z
N	В	2*N+2*B
	total 2073 mm	total total 2073 mm Z N Z

available options of transom lights heights

"N" = 200-800 mm.

available options of the width of transom and side lights

"Z" = 200-1000 mm.

Width of the upper "B" transom lights is adjusted to the width of the fixed door frames; the available options of the width of fixed door frames; available options of the widths can be found in the following tables:

The transom lights are mounted on the single-leaf door frame

	"60"	"70"	"80"	"90"	"100"	"110"
В	688	788	888	988	1088	1188

Transoms mounted with the door frame in double-leaf doors

	"100d"	"110d"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
В	1123	1223	1323	1423	1523	1623	1723	1823	1923	2023	2123

Price of the transom lights/sidelights is calculated per one meter of circumference measured on the outer side of the transom lights/sidelights.

To place an order please contact Atypical Orders Department - phn. 55 236 42 59.

NOTE: The height of the sidelight is adjusted to the standard height of a fixed door frame. Therefore, we do not recommend shortening the door frame in a configuration with the sidelights.











STANDARD OPTIONS

- » door leaf frame made of MDF additionally reinforced with two flat metal bars
- » core made of tubular chipboard
- » external HDF board flat or with decorative milling .
- » 3 silver screw-in pivot hinges
- » straight edge Fig. 1 or edge R 2.5 mm (in CPL laminates, except for white, milky white, gray) Fig. 2

REBATED DOOR LEAF MODEL ENTER:

- » bottom deadbolt lock adapted for door lock cylinder
- » upper deadbolt lock adapted for door lock cylinder
- » Door leaves are available in the investment dimension "90E" (door frame passage with opened door leaf at 90° = 900mm)

REBATED DOOR LEAF SOLID

- » multipoint mortise lock
- » hinges reinforced with anti-thrust bolts
- » Door leaves are available in the investment dimension "90E" (door frame passage with opened door leaf at 90° = 900mm)


APPLICATION

Door leaf ENTER and SOLID can be used as internal entrance door in multifamily and in public utility buildings.

The door leaf frame is made of MDF board, additionally reinforced with two steel flat bars. Filling – tubular chipboard. The doors have increased acoustic insulation (Rw = 32dB), provided that thresholds or a dropping seal are used. HDF external board refined with DRE-Cell Decor - flat finish or with a decorative milling. Door leaf models ENTER/SOLID are available with 0,7 mm CPL laminate - to place an order and for more information please contact Customer Service Department. NOTE: ENTER 0 and SOLID 0 - door leaves in CPL laminates as a standard with an edge radius R 2.5 mm except for white, milky white, gray.

It is reccomended to use together with door leaf collection ENTER/ SOLID fixed door frame

ENTER/SOLID or metal door frames.



* door handle and upper backplate METRO, set of cylinder lock inserts- single key system



ENTER/SOLID 7

ENTER/SOLID 8

ENTER/SOLID 9

ENTER/SOLID 10 ENTER/SOLID 11


ENTER/SOLID 6





















digital viewfinder DDS1 (separately)

digital viewfinder DDS2 (separately)

R 2,5 mm edge in CPL laminate

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » viewfinder included separately
- » digital viewfinder DDS1 included separately » digital viewfinder DDS2 separately
- » stainless steel threshold width 70 mm
- » resignation from the second lock (Enter)
- » dropping seal













STANDARD OPTIONS

- $\ensuremath{\text{\textit{w}}}$ door leaf frame made of MDF additionally reinforced with two flat metal bars
- » core made of tubular chipboard
- » external HDF board flat or with decorative milling .
- » 3 silver screw-in pivot hinges
- » straight edge Fig. 1 or edge R 2.5 mm (in CPL laminates, except for white, milky white, gray) Fig. 2 $\,$

REBATED DOOR LEAF MODEL ENTER:

- » bottom deadbolt lock adapted for door lock cylinder
- » upper deadbolt lock adapted for door lock cylinder
- » Door leaves are available in the investment dimension "90E" (door frame passage with opened door leaf at 90° = 900mm)

REBATED DOOR LEAF SOLID

- » multipoint mortise lock
- » hinges reinforced with anti-thrust bolts
- » Door leaves are available in the investment dimension "90E" (door frame passage with opened door leaf at $90^\circ = 900$ mm)

APPLICATION

Door leaf ENTER and SOLID can be used as internal entrance door in multifamily and in public utility buildings.

It is reccomended to use together with door leaf collection ENTER/ SOLID fixed door frame

ENTER/SOLID or metal door frames.

CONSTRUCTION

The door leaf frame is made of MDF board, additionally reinforced with two steel flat bars. Filling – tubular chipboard. The doors have increased acoustic insulation (Rw = 32dB), provided that thresholds or a dropping seal are used. HDF external board refined with DRECell Decor – flat finish or with a decorative milling.















TER/SOLID 12 ENTER/SOLID 13 ENTER/SOLID 14 ENTER/SOLID 15 ENTER/SOLID 16 ENTER/SOLID 17



ENTER/SOLID 18 ENTER/SOLID 19* ENTER/SOLID 20* ENTER/SOLID 21** ENTER/SOLID 22** ENTER/SOLID 23**


 $^{^{\}ast}$ in models 19 and 20 veneer is glued in strips with variable wood grain.











NOTE: models ENTER 21-23 and SOLID 21-23 - door leaves in CPL laminates and edge with R 2,5 mm radius as a standard.






R 2,5 mm edge in CPL laminate



**in 21-23 models there are 8mm inserts located in one plane with the door leaf surface on both sides





SOLID RC2 - gray oak CPL









STANDARD OPTION:

- » door leaf frame made of soft wood
- » core made of full chipboard
- » straight edge
- » multipoint mortise lock
- » anti-thrust bolts
- » 3 triple hinges
- » HDF external board with aluminum sheet

SOLID RC2 doors have an acoustic insulation class of Rw=32dB and burglary resistance of class RC2 according to PN-EN 1627:2012, provided that the door leaf is completed with a steel door frame, a steel threshold and a separately purchased, dedicated set of fittings: door handle, long backplate and cylinder inserts. Photo of the door handle and long backplate, page 166.

APPLICATION

Door leaf SOLID RC2 can be used as internal entrance door in multifamily buildings and in public utylity buildings. They can be used with door frames:

- » OSS (steel fixed door frame) information and prices page 150
- » OSR (steel adjustable door frame) information and prices page 152
- » OSH (steel hybrid door frame) information and prices page 156



- » viewfinder separately
- » "100" door leaves
- » steel threshold
- » ONTARIO door handle
- » ONTARIO backplate
- » cylinder lock insert (price for 2 pcs.)

OPTIONS WITHOUT EXTRA CHARGE

Door leaves are available in the investment dimension "90E"

(door frame passage with opened door leaf at 90°

= 900mm)







threefold hinge E878



Door frames colours are in two gloss scale (matt/low structure, semi gloss/plain).

FIRE RESISTANT DOOR LEAF ATHOS







ATHOS TECHNICAL REQUIREMENTS: DOORS MEET THE FOLLOWING

- » fire resistance class: El30 with a steel door frame
- » fire resistance class: EI30 with a wooden door frame

Interior entrance door

- » smoke proof class: Sa, S₂₀₀ » mechanical resistance class: 3
- » sound insulation class: RW=32 dB
- » acoustic insulation class: Rw = 37 dB with a wooden door frame and wooden threshold

APPLICATION

Interior entrance fir-resistance doors, are used in residential housing, public utility buildings and collective residential buildings, as well as commercial and technical premises.

STANDARD OPTION

- » door leaf frame made of soft wood
- » core made of full chipboard
- » straight edge
- » single-point mortise lock adapted for cylinder lock
- » 3 triple hinges

DOOR FRAMES

- » steel fixed door frame p. 151
- » steel adjustable door frame p. 153
- » steel hybrid door frame, page 157
- » wooden door frame p. 125

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » DORMATS-71 selfcloser
- » DORMATS-90 selfcloser
- » GEZE TS 2000 selfcloser
- » door leaf "100" (for 0.7 mm laminate)
- » door leaves "100" "110" (for 0.15-0.2 mm laminates)
- » viewfinder
- » wooden threshold

In order to comply with the conditions of the National Technical Assessment, doors with fire resistance EI 30 should be equipped with a selfcloser.

NOTE: The price of the door leaf does not include the price of a steel frame or a wooden frame.

Door leaves with a width of "110" in 0.7 mm laminates available after individual pricing by the Contract Department.



ATHOS 10

CPI Laminate









WOODEN DOOR FRAME

CONSTRUCTION

The OD ATHOS wooden door frame is made of glued pine wood, covered with CPL O laminate, 15-0.2 mm on the display side. The door frame beams with a constant width of 100 mm, are cut at an angle of 90°. An intumescent seal with fire-resistance properties is glued into the channel, milled in the beam rebate.

APPLICATION

OD ATHOS wooden door frames are dedicated to Athos doors, and when installed in accordance with the National Technical Assessment No. 2018/0633, they constitute together with ATHOS door leaf a partition with fire resistance class $El_{\frac{1}{2}}$ 30. Moreover, equipped with a fixed threshold, they meet the acoustic insulation criteria in accordance with Rw = 37 dB class, and in the configuration with a dropping seal, without a fixed threshold, Rw = 32 dB class.


SET CONTAINS

» Main beams (upper beam, latch strike plate beam with installed main lock latch strike plate and hinge beam with the sockets and three-part hinges and and mounted anti-burglary bolt sockets), rebate seal, three hinges (middle part of the three-part hinge) + 3 hinge sockets, set of elements to assemble the door frame according to the attached instructions.

The door frames are packed in a cardboard packaging.

Assortment of wooden frames:

- » OD ATHOS for Athos door with a fixed threshold
- » OD ATHOS UO for Athos doors with a dropping seal




OD dimensions for Athos doors


width.	Α	С	D
"80"	802	910	934
"90"	902	1010	1034
"90E"	917	1025	1049
"100"	1002	1110	1134
"110"	1102	1210	1234

D - width of the assembly hole

Wooden door frame for Athos door with a fixed threshold



Wooden door frame for Athos door with dropping seal *







OPTIONS AVAILABLE WITH EXTRA CHARGE









FORCA TECHNICAL DOORS MEET THE FOLLOWING REQUIREMENTS:

- » class of anti-burglary:
- RC3 (according to PN-EN 1627: 2012)
- » fire resistance class: El₂30
- » smoke proof class: Sa, S

 » mechanical resistance class: 3
- » acoustic insulation class: Rw = 37 dB with a steel frame and a metal threshold

APPLICATION

Fire-resistant and anti-burglary interior entrance doors, used in residential buildings, public buildings and collective housing buildings, as well as utility and technical rooms. The door is sold only as a set with a steel door frame, a steel threshold, a door handle, a long backplate and two cylinder inserts.

STANDARD OPTION

- » door leaf frame made of soft wood
- » core made of full chipboard
- » straight edge
- » steel strings
- » 5-point mortise lock
- » 3 triple hinges

DOOR FRAMES

- » steel fixed door frame p. 151
- » steel adjustable door frame p. 153 » steel hybrid door frame, page 157

- » steel threshold
- » handle-handle F1 color*
- » long backplate F1 color*
- » patent cylinder x 2 pcs.
- » DORMATS-71 selfcloser
- » DORMA TS-90 selfcloser
- » GEZE TS 2000 selfcloser » door leaf "100"
- » viewfinder

In order to meet the conditions of the National Technical Assessment for fire resistance doors with EI 30 and anti-burglary class - a self closer and DIVA door handle with a rlong backplate must be used. Photo of the door handle and a long backplate - page 166.

NOTE: The price of the door leaf should be increased by the price of steel door frame, steel threshold, door handle, backplate and two pcs. of cylinder lock inserts.

- F8 black anode color, available for contract orders, after consultation and individual price verification with the Investment Department.



FORCA 10













FORCA B TECHNICAL DOORS MEET THE FOLLOWING REQUIREMENTS:

- » class of anti-burglary: RC3 (according to PN-EN 1627: 2012)
- » mechanical resistance class: 3
- » acoustic insulation class: Rw = 37 dB with a steel frame and a metal threshold

APPLICATION

Interior entrance doors, with anti-burglary class, used in residential buildings, public buildings and collective housing buildings, as well as utility and technical rooms. The door is sold only as a set with a steel door frame, steel threshold, door handle and long backplate.

STANDARD OPTION

- » door leaf frame made of soft wood
- » core made of full chipboard
- » straight edge
- » steel strings
- » 5-point mortise lock
- » 3 triple hinges

DOOR FRAMES

- » steel fixed door frame p. 151
- » steel adjustable door frame p. 153
- » steel hybrid door frame, page 157

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » steel threshold
- » handle-handle F1 color*
- » long backplate F1 color*
- » patent cylinder x 2 pcs.
- » door leaf "100"
- » viewfinder

NOTE: The price of the door leaf should be increased by the price of steel door frame, steel threshold, door handle, backplate and two pcs. of cylinder lock inserts.

* - F8 black anode color, available for contract orders, after consultation and individual price verification with the Investment Department.



FORCA B 10





OLIMP 10 - white matt





FIRE RESISTANT DOO

OPTIONS AVAILABLE WITH EXTRA CHARGE

Fire-resistance doors are used as interior entrance doors in residential

Assessment self closer should be applied in doors with fire-resistance

housing, public utylity buildings and colective residential buildings. In order to comply with the conditions of the National Technical

REBATED DOOR LEAVES

interior entrance fire-resistance door leaf HALSPAN system

STANDARD OPTIONS

- » core made of Halspan chipboard 44 mm in El30 or 54 mm in El 60 with additional pine wood strips attached circumferentially
- » straight edge, rounded glass pane frame fig.1
- » transparent fire resistance glass pane (variable width dependent upon the size of the door leaf)
- » intumescent smoke-proof gasket
- » 3 hinges
- » cylinder lock
- » dropping seal

fig. 1













» viewfinder

APPLICATION

EI30 and EI60.

» DORMATS-71 selfcloser

» DORMATS-90 selfcloser

» GEZE TS 2000 selfcloser

» fire resistance ventilation grille.

» extra charge for passive door leaf

GEZE TS 2000 self closer

DORMA self closer

DORMATS-90 impuls self closer



Acoustic sound insulation class for single leaf door Rw=32 dB Acoustic sound insulation rate for double leaf door Rw=27 dB

NOTE: In door leaf with fire-resistance EI30 there are used three triple hinges, while in door leaf with fire resistance EI60 there are used VX7939 hinges.









OLIMP 10

OLIMP 20

OLIMP 30

OLIMP EI 60 STEEL FIXED DOOR FRAME


DOOR FRAME CONSTRUCTION

Steel door frame made of 1.5 mm thick structural carbon steel sheet, welded construction, powder coated.

APPLICATION

Door frame is applied to the interior entrance fire-resistance doors $\ensuremath{\mathsf{OLIMP}}$ EI60.

OLIMP EI-60 door leaf vertical cross-section



Olimp EI60 dimensions for single leaf doors

	Α	С	D	Е
"80"	797	867	884	901
"90"	897	967	984	1001
"90E"	926	996	1013	1030
"100"	997	1067	1084	1101
"110"	1097	1167	1184	1201

Olimp EI60 dimensions for double leaf doors

	Α	С	D	Ε
"160"	1633	1703	1720	1737
"170"	1733	1803	1820	1837
"180" = "90" + "90"	1833	1903	1920	1937
"200" = "100" "100"	2033	2103	2120	2137
"210"	2133	2203	2220	2237
"220"	2233	2303	2320	2337

AVAILABLE COLOURS

RAL 9003

Door frame is powder coated in two gloss scale (matt / low structure or semi-gloss / plain). There are available colours:

RAL 7024

brown matt

RAL 8017

white semigloss


RAL 9003



RAL 7047


STANDARD OPTIONS

- » 3 hinges
- » gasket with enhanced flame-resistance properties



D - width of the assembly hole

door frame profile





threefold hinge



Hinge SIMONSWERK VX 7939/160 (for door widths "100" and "110"



WOODEN FIRE RESISTANT DOOR FRA

CONSTRUCTION

Fixed wooden door frame with a cross-section of 54x100 mm (54x120mm for Olimp EI 60 doors) made of coniferous plywood laminated with a 0.2mm CPL laminate in the color of the door leaf.


APPLICATION

The door frame is used for interior fire-resistant entrance doors: OD OLIMP EI30 wooden door frame - for Olimp EI 30 doors OD OLIMP EI60 wooden door frame - for Olimp EI 60 doors


STANDARD OPTIONS

- » 3 hinges
- » gasket with enhanced flame-resistance properties
- » latch strike plate
- » mounting kit


Cross-section of the wooden door frame for OLIMP EI30 doors




Cross-section of the wooden door frame for OLIMP EI60 doors



vertical cross-section of fire-resistance door leaf.



horizontal cross-section door frame in the wall



* dimensions of OD OLIMP EI 30 wooden door frame ** dimensions of OD OLIMP EI 60 wooden door frame

for single-leaf doors

	Α	С	D
80	802	910	934
90	902	1010	1034
90E	917	1025	1049
100	1002	1110	1134
110	1102	1210	1234

door frame for double-leaf doors

	Α	С	D
160	1637	1745	1769
170	1737	1845	1869
180	1837	1945	1969
190	1937	2045	2069
200	2037	2145	2169

OD OLIMP EI30 wooden door OD OLIMP EI30 wooden OD OLIMP EI60 wooden door OD OLIMP EI60 wooden for single-leaf doors

	0		
	Α	С	D
80	804	912	936
90	904	1012	1036
90E	933	1041	1065
100	1004	1112	1136
110	1104	1212	1236

door frame for double-leaf doors

	Α	С	D
160	1640	1748	1772
170	1740	1848	1872
180	1840	1948	1972
200	2040	2148	2172



ENTER ACOUSTIC RW 32 dB











ENTER ACOUSTIC TECHNICAL DOORS MEET THE FOLLOWING REQUIREMENTS:

- » mechanical resistance class: 3
- » sound insulation class Rw = 32dB

APPLICATION

Door leaf ENTER ACOUSTIC are designed to be used as interior entrance door in multifamily buildings and in public utylity buildings

STANDARD OPTION:

- » door leaf frame made of MDF additionally reinforced with two flat metal bars
- » core made of tubular chipboard
- » flat external HDF board
- » dropping seal
- » 3 silver screw-in pivot hinges
- » R2.5mm edge (available only in CPL laminates, except for white, milky white and gray laminates) or straight edge
- » bottom deadbolt lock adapted for door lock cylinder
- » Door leaves are available in the investment dimension "90E" (door frame passage with opened door leaf at 90° = 900mm)

DOOR FRAMES:

- » steel hybrid door frame, page 157
- » steel adjustable door frame p. 153
- » steel fixed door frame p. 151
- » fixed rebated door frame p. 136
- » adjustable door frame with T80, T63 architrave p. 138

OPTIONS AVAILABLE WITH EXTRA CHARGE:

- » viewfinder included separately
- » door leaves "110" except for 0.7 mm laminates

Door leaves with a width of "110" in 0.7 mm laminates available after individual pricing by the Contract Department.



ENTER 0 ACOUSTIC



^{*} decor available while stocks last *** decor only in horizontal grain











GALLA 1 decormat



GALLA 1 decormat brown



GALLA 1 decormat graphite



GALLA 2 sand blasted glass transparent strips



GALLA 3 sand blasted glass transparent strips



GALLA 10 decormat screen printing



transparent glass screen printing



GALLA 11 decormat screen printing



GALLA 11 transparent glass screen printing



GALLA 12 decormat screen printing



GALLA 13 decormat screen printing

Door leaf is made of tempered, 8mm glass pane.

OPTIONS AVAILABLE WITH EXTRA CHARGE

» ventilation undercut available in swing door leaf ((in "80" and "90" meets ventilation requirements)

FITTINGS FOR GLASS DOORS

SELECTION OF LOCKS FOR GLASS DOORS

Glass door locks are universal, they can be configured for left or right sided doors.


In the case of locks in the "toilet" version (with a bathroom knob) - the term "left" or "right" refers to the direction of opening the door: into the bathroom - left lock or into the corridor - right lock (see Fig. 1-4):

Fig. 1-2. For doors opening into the bathroom, select the left lock. Fig. 3-4. Doors opening into the corridor, select the right lock









HARDWARE




^{**} It is necessary to purchase cylinder insert 21/26 separately (see details in the above table)

^{**} Toilet lock - selection of toilet lock see details above



TECHNICAL INFORMATIONS

DOOR LEAF DIMENSIONS AND PLACEMENT OF HARDWARE




The leaf is a glass pane, made of safe, uniform tempered glass, 8 mm thickness, with holes for mounting:

- » hinges and lock in swing doors leaf
- » round door handle and hardware adapted for sliding system door leaf


APPLICATION

Glass door leaf are used as interior doors in residential housing, public utility buildings and collective residential buildings.

OPENING DIRECTION OF GLASS DOOR LEAF



There are two different sides of glass pane in Galla door leaves (does not refer to transparent Galla1).



DOOR LEAF WIDTH

Symbol of the door dimension	SZ	SZP
"60"	617	630
"70"	717	730
"80"	817	830
"90"	917	930

SZ - width of glass swing door leaf

SZP - width of glass sliding door leaf

DOOR LEAF HEIGHT

2036 mm - height of glass swing door leaf 2054 mm - height of glass sliding door leaf

NOTE: . There is no possibility to shorten glass door leaf.

CLEARANCE BETWEEN DOOR LEAF AND FLOOR

Standard clearance between door leaf unit and ready floor is 8 mm.

NOTES REFERED TO HINGE


DOOR FRAMES applied to glass doors should be equipped with two pivot .00 $15\ \mathrm{mm}$.

FULFILMENT OF VENTILATION REQUIREMENTS FOR GLASS DOORS

	doors with ventilation undercut			
symbol dim. DOORS	ventilation surface of the undercut and the clearance 8 mm [m2]	required clearance to meet ventilation requirements [in mm]		
"90"	0,027	2		
"80"	0,024	5,5		
"70"	0,021	10*		
"60"	0,017	16*		

* - door leaf "60" and "70" doesnt meet ventilation requirements.

Ventilation undercut (only active door leaf)



In order to meet ventilation requirement - total ventilation surface 0,022 m2, there must be used ventilation undercut in active glass door leaf with "80" - "90" width and standard clearance between door leaf and floor (8mm).

FIXED DOOR FRAMES

CONSTRUCTION

Fixed door frame is made of high-quality wood-based board and it is coated with ecological, wood-like decorative DRE-Cell veneer, 3D veneer, 0,15 - 0,20 mm CPL, finish veneer or painted.

Door frames has fixed width of 100 mm.

ΔΡΡΙΙΟΔΤΙΟΝ

Fixed door frame can be used in the following types of doors:

- » ENTER entrance doors (equipped with 3 ø 13,5 mm hinges and additional upper latch plate)
- » SOLID entrance doors (equipped with 3 ø 13,5 mm hinges and 4 hooks for the latch and latches of the flat multi-point lock)
- » glass doors ("OPC" they are equipped with two hinges \emptyset 15 mm, special latch plate and rubber seal strip)
- » other remaining rebated door leaf (using 2 or 3 ø 13,5 mm hinges, in all frame construction door and panel door collections having size "90" and wider; door frames should be equipped with 3 hinges)

Masking architraves are used in fixed door frames and SOFT door frames, whereas for natura fixed SOFT door frames angular architrave are used.


THE SET CONTAINS

Main beam (horizontal element and two vertical elements), door seal, set of hinges, set of elements intended for assembling the door frame according to the attached instructions. Door frames are packed in cardboard boxes.







OP profile




OP SOFT profile



OP vertical cross-section for rebated door leaf




OP vertical cross-section for glass doors



required height of wall passage 2089 mm (2095 mm for glass doors)

OP Horizontal cross section



for single-leaf doors

•					
	A C		D		
"60"	600	688	712		
"70"	700	788	812		
"80"	800	888	912		
"90"	900	988	1012		
"90E"	904	992	1016		
"100"	1000	1088	1112		
"110"	1100	1188	1212		

^{*} door frames for glass doors, width "60" - "90"

D - required width of wall opening

for rebated door leaf double-leaf doors

	Α	С	D		
"100d"	1035	1123	1147		
"110d"	1135	1223	1247		
,120"	1235	1323	1347		
,130"	1335	1423	1447		
,140"	1435	1523	1547		
,150"	1535	1623	1647		
,160"	1635	1723	1747		
,170"	1735	1823	1847		
,180"	1835	1923	1947		
,190"	1935	2023	2047		
,200"	2035	2123	2147		

OPTIONS AVAILABLE WITH EXTRA CHARGE

- » door frame ENTER (with latch deadbolt plate)
- » door frame SOLID
- » door frame for double leaf door:

+30%

CONSTRUCTION

Fixed non-rebated door frame is made of high-quality wood-based board and it is coated with ecological, wood-like decorative DRE-Cell veneer, 3D veneer, 0,15 - 0,20 mm CPL or painted. Door frames has fixed width of 100 mm.

APPLICATION

Fixed non-rebated door frame can be applied to all DRE collections which are available in non-rebated option.

SET CONTAINS


Main beam (horizontal element and two vertical elements), door seal, set of hinges, set of elements intended for assembling the door frame according to the attached instructions. Door frames are packed in cardboard boxes.




OPB vertical cross-section

2082 2082 2042 8 gloor

OPB Horizontal cross section





required height of the wall opening 2097 mm

D - required width of wall opening

for single-leaf doors

	Α	С	D	
"60"	627	707	730	
"70"	727	807	830	
"80"	827	907	930	
"90"	927	1007	1030	
"100"	1027	1107	1130	

for double-leaf doors

	Α	С	D	
"120"	1274	1354	1380	
"130"	1374	1454	1480	
"140"	1474	1554	1580	
"150"	1574	1654	1680	
"160"	1674	1754	1780	
"170"	1774	1854	1880	
"180"	1874	1954	1980	

Prices include 2 hinges with assembly plates.

Price of the double-leaf door frame: \pm 50% (if 3 hinges are used, there is extra charge)

» Additional payment for the third hinge Estetic 80

ADJUSTABLE DOOR FRAMES

REBATED WITH T80 OR T63 ARCHITRAVE

CONSTRUCTION

The adjustable door frame with T80 or T63 architrave is equipped with angle brackets with small rounding radii of the cross profile. It is made of high-quality wood-based board. On the display side, it is entirely covered with wood-like decorative foil DRE-Cell Decor , 3D foil, and CPL laminate thickness. 0.15 - 0.2 mm or painted ** . Its design allows for use on walls with a thickness of 60 - 320 mm. Connecting at a 90° angle is available with T80 architrave in white matt, black 2 matt, white UV acrylic painted, white pine, sand oak, 3D Polish oak.

**NOTE: To ensure the highest quality of painted door frames, before painting process they are coated with special material which constitues solid base.



OR (adjustable rebated door frame) with T63

APPLICATION

Adjustable door frame can be applied for:

- » interior door leaves rebated and for glass door leaves (ORC)
- » entrance doors ENTER (includes 3 hinges ø 13, 5 mm, additional latch plate extra charge net)

SET CONTAINS

Main beam (one horizontal and two vertical elements together with masking elements), door seal, set of hinges, all necessary components for the instalation of door frames in accordance with the supplied instruction. Door frames are packed in cardboard boxes.

Door frames are packed in cardboard boxes.

All door frames for the frame construction doors and door frames 90 mm and wider should be equipped with 3 hinges. Glass door frames are equipped with 2 hinges \emptyset 15 mm, a special catch and a seal.




OR (adjustable rebated door frame) with T80


Price of adjustable door frame for double leaf door: +30%The door frame for wall thickness 060-075 has got a shallower milling on the movable architrave side during assembly it is necessary to shorten the tongue of the architrave. Extra charge for 90° joining in white matt, black matt 2, white UV acrylic varnish, white pine, sand oak, Polish 3D oak Extra charge for reinforcement for self closer applies to door frames with 45° connection angle^{about}

ADJUSTABLE DOOR FRA REBATED WITH T80 OR T63 ARCHITRAVE


Cross-section of rebated door frame OR/ door frame for glass doors ORC with the architrave. T63



Cross-section of rebated door frame OR/ door frame for glass doors ORC with the architrave. T80



OR/ORC horizontal cross-section



D - required width of wall opening

for double-leaf doors

	Α	С	D	E**	E*
100d	1035	1079	1115	1219	1185
110d	1135	1179	1215	1319	1285
120	1235	1279	1315	1419	1385
130	1335	1379	1415	1519	1485
140	1435	1479	1515	1619	1585
150	1535	1579	1615	1719	1685
160	1635	1679	1715	1819	1785
170	1735	1779	1815	1919	1885
180	1835	1879	1915	2019	1985
190	1935	1979	2015	2119	2085
200	2035	2079	2115	2219	2185


* dimension reffer to door frame with T63 architrave

** dimension reffer to door frame with T80 architrave

for single-leaf doors


	Α	С	D	E**	E*
60	602	646	680	786	752
70	702	746	780	886	852
80	802	846	880	986	952
90	902	946	980	1086	1052
90E	906	950	984	1090	1056
100	1002	1046	1080	1186	1152
110	1102	1146	1180	1286	1252

Adjustable door frame connection




Joining at an angle of 90° available in white matt, black matt 2, white painted acrylic UV, white pine, sand oak, Polish 3D oak.

vertical cross-section of rebated door leaf with OR



vertical cross-section of glass doors with ORC



required wall passage height 2066 mm (2072 mm for glass doors)

Black ST decor available only with T80 architrave

Price of adjustable door frame for double leaf door: +30%

The door frame for wall thickness 060-075 has got a shallower milling on the movable architrave side

during assembly it is necessary to shorten the tongue of the architrave.

Extra charge for 90 ° joining in white matt, black matt 2, white UV acrylic varnish, white pine, sand oak, Polish 3D oak

Extra charge for reinforcement for self closer applies to door frames with 45° connection angle about

2nd group CPL - CPL laminate natural halifax oak.

NON-REBATED ADJUSTABLE DOOR FRAMES

NON-REBATED WITH T80 OR T63 ARCHITRAVE

CONSTRUCTION

The non-rebated adjustable door frame is made of high-quality wood-based board. On the display side, it is entirely covered with wood-like decorative foil DRE-Cell Decor , 3D foil, CPL laminate or painted**. Its construction allows to be used with door leaf with the thickness of 40 mm and its design allows for use on walls ranging between 75-320. There is possibility to choose the beam joining angle of 90° with the T80 architrave in decors white matt, black 2 matt, UV acrylic painted white, white pine, sand oak, 3D Polish oak, lacquered white, lacquered black, decors from the LUX and WOOD collections.


**NOTE: To ensure the highest quality of painted and lacquered door frames, before varnishing or painting process they are coated with special material which constitues solid base.

APPLICATION

The adjustable non-rebated door frame with Estetic 80 hinges is applicable to all DRE collections in the non-rebated version with Estetic 80 hinges. The non-rebated adjustable door frame with plate hinges is suitable for the Sigma collection in matt black 2, lam_white, lam_white craft oak veneers.

THE SET CONTAINS


Main beam (horizontal element and two vertical elements) with a wide architrave (80 mm) with small rounding radii of the cross-section profile (R2), door seal, set of hinges, set of elements intended for assembling the door frame according to the attached instructions. Door frames are packed in cardboard boxes.




Prices include 2 hinges with assembly plates.

- » Price of the door frame for double-leaf doors: +50% (with 3 Estetic 80 hinges, extra charge)
- » Extra charge for the third Estetic 80 hinge
- » Price of the door frame for double-leaf doors: +50% (with 3 plate hinges, extra charge)
- » Extra charge for the third plate hinge
- » Extra charge for connection of main beams at 90° available in white matt, black matt 2, white UV varnish, white pine, sand oak, Polish oak 3D, white varnish, black varnish and LUX and WOOD collection sdecors
- » Extra charge for reinforcement for self closer applies to door frames with 45° connection angle about

NON-REBATED ADJUSTABLE DOOR FRAM






non-rebated door leaf T63 2117 / T80 2134 2079 2064 2043 mi. 2042


Vertical section of the door

required wall passage height 2079 mm

ORB connection at 45°




Adjustable non-rebated door frame connection at an angle of 90° T80 architrave



** connection at 90° is available in white matt, black matt 2, white acrylic UV varnish, white pine, sand oak, Polish oak 3D, white varnish, black varnish and LUX and WOOD collections

ORB horizontal cross-section



D - required width of wall opening

E1 - dimension for T63 architrave E2 - dimension for T80 architrave

*075-095 door frame has a different cross section, for 75-89 mm wall thickness, it is necessary to shorten the tongue of the adjustable architrave.

for double-leaf doors

	Α	С	D	E1	E2
120	1274	1318	1350	1424	1458
130	1374	1418	1450	1524	1558
140	1474	1518	1550	1624	1658
150	1574	1618	1650	1724	1758
160	1674	1718	1750	1824	1858
170	1774	1818	1850	1924	1958
180	1874	1918	1950	2024	2058

for single-leaf doors

	Α	С	D	E1	E2
60	627	671	700	777	811
70	727	771	800	877	911
80	827	871	900	977	1011
90	927	971	1000	1077	1111
100	1027	1071	1100	1177	1211

Prices include 2 hinges with assembly plates.

- Price of the door frame for double-leaf doors: +50% (with 3 Estetic 80 hinges, extra charge)
- Extra charge for the third Estetic 80 hinge
- » Price of the door frame for double-leaf doors: +50% (with 3 plate hinges, extra charge)
- Extra charge for the third plate hinge
 Extra charge for connection of main beams at 90° available in white matt, black matt 2, white UV varnish, white pine, sand oak, Polish oak 3D, white varnish, black varnish and LUX and WOOD collections decors
- » Extra charge for reinforcement for self closer applies to door frames with 45° connection angle about

2nd group CPL - CPL laminate natural halifax oak.

REBATED WITH VARIABLE HEIGHTS WITH T80 ANGLE BAR

By the fact of the interest expressed by our clients in doors of custom sizes, we have introduced to our offer collections of MODERN, PLUS and STANDARD 10 door leaf model with adjustable door frame equipped with angular architrave T80 in 3 additional heights.


APPLICATION

Adjustable door frame with variable heights with T80 architrave can be used for rebated door leaf STANDARD 10, MODERN and PLUS collections with three additional leaf height options: 1983mm, 2110mm and 2240mm.

SET CONTAINS

Main beam (one horizontal and two vertical elements together with masking elements), door seal, set of hinges, all necessary components for the instalation of door frames in accordance with the supplied instruction. Door frames are packed in cardboard boxes. Door frames are packed in cardboard boxes.

All rebated door frames in 3 additional height options should be equipped with 3 hinges.



Ī	1	7			wall
Hc	04	Hw	H\$		T

OR vertical cross-section

Н	HŚ	hw	НО	НС
1983	1969	1991	2006	2061
2110	2096	2118	2133	2188
2240	2226	2248	2263	2318

for single-leaf doors

	Α	С	D	Е			
60	602	646	680	786			
70	702	746	780	886			
80	802	846	880	986			
90	902	946	980	1086			
100	1002	1046	1080	1186			


for double-leaf doors

	Α	С	D	Е			
120	1235	1279	1315	1419			
130	1335	1379	1415	1519			
140	1435	1479	1515	1619			
150	1535	1579	1615	1719			
160	1635	1679	1715	1819			
170	1735	1779	1815	1919			
180	1835	1879	1915	2019			
190	1935	1979	2015	2119			
200	2035	2079	2115	2219			


Black ST decor available only with T80 architrave



Cross-section of rebated door frame OR with the architrave. T80



OR horizontal cross-section



D - required width of wall opening

H - door leaf height H0 - required the wall passage height

Extra charge for reinforcement for self closer applies to door frames with 45° connection angle about

NON-REBATED ADJUSTABLE DOOR FRAMES

NON-REBATED WITH VARIABLE HEIGHTS WITH T80 ARCHITRAVE

Due to customers' interest in non-rebated doors in non-standard dimensions, we have introduced the Modern and Plus collections and the Standard 10 door leaf model with an adjustable non-rebated door frame in 3 additional height variants. The structure of the door frame is the same as the non-rebated adjustable door frame (the only difference is the height).

APPLICATION

Non-rebated adjustable door frame with variable heights can be used with non-rebated STANDARD 10, MODERN and PLUS door leaf model which are available in three additional door leaf height options:1983 mm, 2110 mm and 2240 mm.

SET CONTAINS


Main beam (one horizontal and two vertical elements together with masking elements), door seal, set of hinges, all necessary components for the instalation of door frames in accordance with the supplied instruction. Door frames are packed in cardboard boxes. Door frames are packed in cardboard boxes.

All door frames in 3 additional height options can be equipped with 2 or 3 hinges.




Н	HŚ	hw	НО	HC
1983	1982	2004	2019	2074
2110	2109	2131	2146	2201
2240	2239	2261	2276	2331

ORB cross-section 095-300




ORB cross-section 075



for single-leaf doors

	Α	С	D	E
60	627	671	700	811
70	727	771	800	911
80	827	871	900	1011
90	927	971	1000	1111
100	1027	1071	1100	1211

ORB vertical cross-section




for double-leaf doors

	Α	C	D	E
120	1274	1318	1350	1458
130	1374	1418	1450	1558
140	1474	1518	1550	1658
150	1574	1618	1650	1758
160	1674	1718	1750	1858
170	1774	1818	1850	1958
180	1874	1918	1950	2058

H0 - required the wall passage height

ORB horizontal cross-section



*NOTE: 075-095 door frame has a different crosssection, for a 75-89 mm wall thickness, it will be necessary to shorten pen of the adjustable angle element.

D - required width of wall opening

Black ST decor available only with T80 architrave

Prices include 2 hinges with assembly plates.

Price of the double-leaf door frame: \pm 50% (if 3 hinges are used, there is extra charge)

- » Additional payment for the third hinge Estetic 80
- » Extra charge for reinforcement for self closer applies to door frames with 45° connection angle about

NON-REBATED ADJUSTABLE DOOR FRAMES

FOR DOOR LEAVES WITH INVERTED REBATE

CONSTRUCTION

The adjustable door frame with inverted rebate is made of high-quality wood-based board. On the display side, it is covered with ecological, wood-like decorative foil DRE Cell, CP black ST or painted with the highest quality acrylic UV varnishes. To ensure high quality of painted door frames, before painting, they are covered with a special material constituting a uniform base. Its design is adapted to a door leaf thickness of 40 mm and allows for use on walls with a thickness of 90 - 290 mm. Joining at an angle of 45° .


APPLICATION


The door frame with invreted rebate is suitable for selected collections: Estra, Nestor, Nova Cell Uni, Binito, Fargo.

THE SET CONTAINS


Main beam (horizontal element and two vertical elements), T80 architrave (horizontal and two vertical elements), door seal, set of two Estetic 1821 hinges, magnetic lock latch strike plate, set of elements for assembling the door frame according to the attached instructions. Door frames are packed in cardboard boxes.












Estetic 1821 hinge

DRE-Cell Decor





	Α	С	D	Е	F	S
60	625	694	724	785	834	644
70	725	794	824	885	934	744
80	825	894	924	985	1034	844
90	925	994	1024	1085	1134	944
100	1025	1094	1124	1185	1234	1044
90	925	994	1024	1085	1134	944









sage oak

white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R

ashen - RAL 7035

An adjustable tunnel is a decorative element of a wall passage. It can be used as a stand-alone solution or as an integral part of the NT wall sliding system.

The adjustable tunnel is a product which is, at first glance visually similar to adjustable door frames, but with a few differences:

- there is no possibility to mount any hinges
- there is no latch strike plate
- there is no channel for a gasket different heights and spans of the front and rear architraves (values E and F in tables)

Vertical cross-section of Vertical cross-section of TUN tunnel cross-section with the architrave. T80 an adjustable tunnel with an adjustable tunnel with architrave. T80 architrave. T63 C max TUN tunnel cross-section with the architrave. T63 2127 min. 2057 2035 2035 C max

NOTE: To ensure the highest quality of painted tunnels, before painting process they are coated with special material which constitutes solid base.

required height of wall opening 2067 mm

floor


Single adjustable tunnel

symbol	60	70	80	90	100
Α	602	702	802	902	1002
С	646	746	846	946	1046
D	664	764	864	964	1064
E*	752	852	952	1052	1152
E**	786	886	986	1086	1186
F*	736	836	936	1036	1136
F**	770	870	970	1070	1170

D - required width of wall opening * applies to the Adjustable Tunnel with architrave. T63 ** applies to the Adjustable Tunnel with an architrave. T80

OPTIONS AVAILABLE WITH EXTRA CHARGE

Tunnel for double leaf door: +30%



Adjustable tunnel cross section

E* / E**


Black ST decor available only with T80 architrave


Double adjustable tunnel

	,																		
symbol	120	130	140	150	160	170	180	190	200	symbol	120	130	140	150	160	170	180	190	200
Α	1200	1300	1400	1500	1600	1700	1800	1900	2000	E**	1384	1484	1584	1684	1784	1884	1984	2084	2184
С	1244	1344	1444	1544	1644	1744	1844	1944	2044	F*	1334	1434	1534	1634	1734	1834	1934	2034	2134
D	1264	1364	1464	1564	1664	1764	1864	1964	2064	F**	1368	1468	1568	1668	1768	1868	1968	2068	2168
E*	1350	1450	1550	1650	1750	1850	1950	2050	2150	2nd group CPL - CPL laminate natural halifay oak									



UNI 10 - white







white acrylic UV varnish - RAL 9003 ecru - RAL 9001 latte - Flugger 4362, NCS S1505-Y50R ashen - RAL 7035

Price of the set = price of two vertical beams + price of the horizontal beam with architrave panels

CONSTRUCTION


The non-rebated adjustable door frame is made of high-quality wood-based board. The display side is entirely covered with a special foil and then painted. Its construction allows to be used with door leaf with the thickness of 40 mm and its design allows for use on walls ranging between 75-320. There are special angle panels in the lintel on both sides of the door frame, with the following dimensions: 80 mm, 180 mm or 900 mm.


APPLICATION

Adjustable non-rebated door frame with architrave panels can be used with all DRE non-rebated painted collections.


SET CONTAINS


Vertical beams with wide architrave (80 mm) with small rounding radii of the cross-section profile (R2), upper beam with angle panels to choose from, door seal, set of hinges, set of elements for assembling the door frame according to the attached instructions. Door frames are packed in cardboard boxes.





cross-section of vertical beam






B-B Horizontal cross-section

*NOTE: 075-095 door frame has a different cross-section, shallow milling for architrave, for a 75-89 mm wall thickness, it will be necessary to shorten the tongue of the adjustable masking architrave.

** - third hinge, option at extra charge



D - required width of wall opening

	for single-leaf doors									
	С	D	Е							
Ī	174	700	044							

	Α	С	D	Е
60	627	671	700	811
70	727	771	800	911
80	827	871	900	1011
90	927	971	1000	1111
100	1027	1071	1100	1211

EXTENSION PANELS


APPLICATION

The extension panel is a component of the decorative passage in the wall or the increased possibility of installing door frames on walls thicker than 320 mm. The panel is an extension of the central parts of the adjustable door frames and adjustable tunnels. It can be used with the adjustable architraves from previously ordered door frames or tunnels with a connection angle of 45°.


Extention panels with variable heights are available only in Cell and CPL group.


SET CONTAINS

- » two vertical beams
- » horizontal beam
- » three connecting tongues
- » accessories used to connect main beams









options of the width of panels cross-section

X	062	082	107	127	147	167	187	207	227	247	267	287
---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

EXTENSION PANELS

Dimensions of extension panels OR - adjustable door frames for rebated doors

	height options										
	PL	198x	211x	224X							
HŚ	2029	1969	2096	2226							
hw	2051	1991	2118	2248							

		for single-leaf doors						for single-leaf doors for double-leaf doors											
	"60"	"70"	"80"	"90"	"100"	"110"	"100d"	"110d"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"		
Α	602	702	802	902	1002	1102	1035	1135	1235	1335	1435	1535	1635	1735	1835	1935	2035		
С	646	746	846	946	1046	1146	1079	1179	1279	1379	1479	1579	1679	1779	1879	1979	2079		

Dimensions of the ORB extension panels connected at 45 $^{\circ}$ - non-rebated adjustable door frames for non-rebated doors connected at 45 $^{\circ}$

	height options									
	PL	198x	211x	224X						
HŚ	2042	1982	2109	2239						
hw	2064	2004	2131	2261						

	for single-leaf doors for double-leaf doors											
	"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"
Α	627	727	827	927	1027	1274	1374	1474	1574	1674	1774	1874
С	671	771	871	971	1071	1318	1418	1518	1618	1718	1818	1918

Dimensions of TUN extension panels - adjustable tunnels

	PL	
HŚ	2035	ſ
hw	2057	

2057

НŚ 2035

			for si	ngle-leaf	doors			for double-leaf doors							
		"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
Ì	Α	602	702	802	902	1002	1200	1300	1400	1500	1600	1700	1800	1900	2000
ĺ	С	646	746	846	946	1046	1244	1344	1444	1544	1644	1744	1844	1944	2044

Dimensions of the ORC extension panels

- adjustable door frames for glass doors

Dimensions of the ORS extension panels - adjustable door frames for folding doors Dimensions of ORO extension panels

	"60"	"70"	"80"	"90"
Α	600	700	800	900
_	/ 4 4	744	044	044

	PL		"80"	"90"	"100"
HŚ	2029	Α	806	906	1006
hw	2051	С	850	950	1050

- adjustable door fra	mes for doo	leaves with	inverted re	bate

	PL		"60"	"70"	"80"	"90"	"100"
НŚ	2066	Α	650	750	850	950	1050
hw	2088	С	694	794	894	994	1094

OPTIONS AVAILABLE WITH EXTRA CHARGE

panel for double doors: + 30%

STEEL FIXED DOOR FRAMES

CONSTRUCTION

Steel door frames are made of 1.5 mm thick low-carbon steel sheet, protected with a protective organic varnish coating. The door frame consists of two beams: a catch beam and a hinge beam (in the case of double-leaf door frames there only two hinge beams) and the upper beam, permanently connected to each other by welding. Hinge beams are equipped with hinge sockets, while catch beams have cutouts for the tongue and latches for the lock of a dedicated door leaf (the set includes a cover seal). The profile of the door frame, its dimensions, equipment and colors depend on the selected variant - the type of door for which the door frame is to be used.

APPLICATION / TYPES OF OSS DOOR FRAMES (FIXED STEEL DOOR FRAMES)

OSS_STAND
OSSB_STAND
OSSB_STAND
OSS for non-rebated interior doors
OSS_GLASS
OSS for interior glass doors

OSS_ENTER OSS for the Enter door, Enter Akustik, Revos

OSS_SOLID OSS for solid doors
OSS_SOLID_RC2 OSS for Solid RC2 door leaf
OSS_ATHOS OSS for Athos door leaf
OSS_FORCA OSS for Forca or Forca B door leaf
OSS_OLIMP_EI30 OSS for Olimp EI-30 door leaf

All frames are designed to be mounted on the finished floor.

STANDARD OPTIONS IN OSS

- » sockets for 2, 3, 4 or 6 hinges
- » socket for latch plate of main lock

STANDARD OPTIONS IN OSSB

- » sockets for 2 or 4 hinges
- » magnetic lock latch

STANDARD OPTIONS IN OSS GLASS

- » sockets for 2 hinges
- » socket for latch plate of main lock

STANDARD OPTIONS IN OSS ENTER

- » sockets for 3 hinges
- » socket for main lock or additionally for upper lock

STANDARD OPTIONS IN OSS SOLID

- » sockets for 3 hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch bolts of multi-point lock used in SOLID model

STANDARD OPTIONS IN OSR SOLID RC2

- » sockets for 3 triple hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch bolts of multi-point lock used in SOLID model

STANDARD OPTIONS IN OSS ATHOS, FORCA, FORCA B


- » sockets for 3 triple hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch plates of five point mortise lock (FORCA, FORCA B)
- » socket for latch plate of main lock (ATHOS)

STANDARD OPTIONS FOR OSS OLIMP EI30

- » socket for latch plate of main lock
- » sockets for 3 or 6 triple hinges (6 for double-leaf frames)

AVAILABLE COLOURS


Door frame is powder coated in two gloss scale (matt / low structure or semi-gloss / plain). There are available colours:




*** beige colour is available only in semi-gloss



STEEL FIXED DOOR FRAMES





НО	HŚ	hw	hm	W	SZP	
2084	2040,5	2075,5	2089	46	106	
. .		<i>_</i> _				
2071	2027,5*	2062,5	2076	30	90	
2077	2033,5	2068,5	2082	30	90	
2072	2020 5*	20/45	2070			
20/3	2029,5	2004,5	20/8	38	117	
2070	2025,5	2060,5	2074			
	2084 2071 2077 2073 2070	2084 2040,5 2071 2027,5* 2077 2033,5 2073 2029,5*	2084 2040,5 2075,5 2071 2027,5* 2062,5 2077 2033,5 2068,5 2073 2029,5* 2064,5 2070 2025,5 2060,5	2084 2040,5 2075,5 2089 2071 2027,5* 2062,5 2076 2077 2033,5 2068,5 2082 2073 2029,5* 2064,5 2078 2070 2025,5 2060,5 2074	2084 2040,5 2075,5 2089 46 2071 2027,5* 2062,5 2076 30 2077 2033,5 2068,5 2082 30 2073 2029,5* 2064,5 2078 38 2070 2025,5 2060,5 2074	

Α Ε D - width of the assembly hole OSS glass doors OSS SOLID RC2 OSS width dimensions **OSS STAND** OSS ATHOS **OSS ENTER OSS FORCA** OSS SOLID symbol Α C D Ε width. "60" 600 670 687 697 • "70" 700 770 787 797 • • "80" 800 870 887 897 •

• • • • • •

•

•

• •

• • • •

> • •

> • •

wall

"90"

"90E"

"90E"

"100"

"110"

900

904

915

1000

1100

970

974

985

1070

987

991

1002

1087

997 •

1001

1012

1097

•

•

OSS OLIMP EI30 for single leaf door

wall

symbol width.			D	Е	
"80"	802	872	889	899	
"90"	902	972	989	999	
"90E"	917	987	1004	1014	
"100"	1002	1072	1089	1099	
"110"	1102	1172	1189	1199	

OSS STAND dimensions

for double leaf doors

symbol A width.		С	D	Е
"100d"	1032	1102	1119	1129
"110 _D "	1132	1202	1219	1129
"120"	1232	1302	1319	1329
"130"	1332	1402	1419	1429
"140"	1432	1502	1519	1529
"150"	1532	1602	1619	1629
"160"	1632	1702	1719	1729
"170"	1732	1802	1819	1829
"180"	1832	1902	1919	1929
"190"	1932	2002	2019	2029
"200"	2032	2102	2119	2129

OSS OLIMP EI30 for double leaf doors

symbol width.	ymbol A vidth.		D	Е
"160"	1637	1707	1724	1734
"170"	1737	1807	1824	1834
"180"	1837	1907	1924	1934
"190"	1937	2007	2024	2034
"200"	2037	2107	2124	2134
"210"	2137	2207	2224	2234
"220"	2237	2307	2324	2334

OSSB STAND for single leaf door

symbol width.	Α	С	D	Е	
"60"	624	694	711	721	
"70"	"70" 724		811	821	
"80"	80" 824		911	921	
"90"	924	994	1011	1021	
"100" 1024		1094	1111	1121	

OSSB STAND for double leaf doors

symbol width.	Α	С	D	Е
"120"	1271	1341	1358	1368
"130"	1371	1441	1458	1468
"140"	1471	1541	1558	1568
"150"	1571	1641	1658	1668
"160"	1671	1741	1758	1768
"170"	1771	1841	1858	1868
"180"	1871	1941	1958	1968

 $^{^{\}ast}$ - STAND steel fixed door frames for double leaf door "100d" - "200" width

Hś - height of the door frame passage

^{* -} with the use of a steel threshold - the actual height of the door frame passage will be reduced by 20mm from the floor

^{1170 | 1187 | 1197 |} **** - investment dimension "90E" different for technical and remaining doors

^{** -} OSS FORCA B - OSS FORCA option for Forca B doors (without fire resistance)

^{*** -} steel fixed non-rebated OSSB STAND single-leaf door frames with 3 hinges, extra charge $\,$, for double-leaf doors with 6 hinges, extra charge of

ADJUSTABLE METAL DOOR FRAME

The essence of an adjustable door frame is that it allows the final closure of the wall opening without the need to finish the wall. The extension of the door frames closing architrave, allows for adjustment in the range of +30mm

APPLICATION / TYPES OF OSR (ADJUSTABLE STEEL DOOR FRAMES)

OSR STAND OSR For rebated interior doors **OSRB STAND** OSR for non-rebated interior doors

OSR_GLASS OSR For interior glass doors

OSR_ENTER OSR for the door leaf Enter, Enter Akustik, Revos

OSR_SOLID OSS for solid doors OSR SOLID RC2 OSR for Solid RC2 OSR ATHOS OSR for Athos door leaf

OSR_FORCA OSR for Forca or Forca B door leaf OSR_OLIMP EI 30 OSS for Olimp EI-30 door leaf OSR_OLIMP EI 60 OSR for Olimp EI 60 doors

All frames are designed to be mounted on the finished floor.

The door frames are suitable for walls with a thickness of 95-305 mm, 103-313 mm in the case of steel adjustable door frames OSR FORCA, steel adjustable door frames OSR ATHOS and steel adjustable door frames OSR OLIMP EI30 or 113-323 mm in the case of steel adjustable door frames OSR OLIMP EI 60. For a given wall thickness, select the appropriate door frame variant, the range of which Cmin - Cmax will include the thickness of the finished wall.

CONSTRUCTION

Steel door frames are made of 1.5 mm thick low-carbon steel sheet, powder-coated. The door frame consists of two beams: a catch beam and a hinge beam (in the case of double-leaf door frames there only two hinge beams) and the upper beam, permanently connected to each other by welding. Hinge beams are equipped with hinge sockets, while catch beams have cutouts for the tongue and latches for the lock of a dedicated door leaf (the set includes a cover seal). The outer and inner sides of the door frame are protected with a protective, organic varnish coating. The profile of the door frame, its dimensions and equipment depend on the selected variant - the type of door for which the door frame is to be used.

STANDARD OPTIONS IN OSR STAND

- » sockets for 2, 3, 4 or 6 hinges
- » socket for latch plate of main lock

STANDARD OPTIONS IN OSRB STAND

- » sockets for 2 or 4 hinges
- » magnetic lock latch

STANDARD OPTIONS IN OSR GLASS DOORS

- » sockets for 2 hinges
- » socket for latch plate of main lock

STANDARD OPTIONS IN OSR ENTER

- » sockets for 3 hinges
- » socket for main lock or additionally for upper lock

STANDARD OPTIONS IN OSR SOLID

- » sockets for 3 hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch bolts of multi-point lock used in SOLID model

STANDARD OPTIONS IN OSR SOLID RC2

- » sockets for 3 triple hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch bolts of multi-point lock used in SOLID model

STANDARD OPTIONS IN OSR ATHOS, FORCA, FORCA B

- » sockets for 3 triple hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch plates of five point mortise lock (FORCA, FORCA B)
- » socket for latch plate of main lock (ATHOS)

STANDARD OPTIONS FOR OSR OLIMP EI30

- » sockets for 3 threefold hinges
- » socket for latch plate of main lock


AS STANDARD STEEL ADJUSTABLE DOOR FRAME OSR OLIMP EI 60

- » sockets for 3 pcs. of three-part or object hinges
- » socket for latch plate of main lock

AVAILABLE COLOURS

Door frame is powder coated in two gloss scale (matt / low structure or semigloss / plain). There are available colours:







Black semi-gloss

black matt

Adjustable steel rebated door frames - dimensions






 st - with the use of a steel threshold - the actual height of the door frame passage will be reduced by 20mm from the floor

D - width of the wall opening

OSR door frame profile with the T57 architrave



** 91 for steel adjustable door frame OSR ATHOS, OSR FORCA, OSR FORCA B and OSR OLIMP EI 30

OSR OLIMP EI30 for single leaf door

symbol width.	Α	D	Е	F
"80"	802	892	921	921
"90"	902	992	1021	1021
"90E"	917	1007	1036	1036
"100"	1002	1092	1121	1121
"110"	1102	1192	1221	1221

steel adjustable door frame OSR OLIMP El60 for single leaf door

symbol width.	А	D	Е	F
"80"	797	894	923	916
"90"	897	994	1023	1016
"90E"	926	1023	1052	1045
"100"	997	1094	1123	1116
"110"	1097	1194	1223	1216

C

OSR width di	mensio	ns		OSR_STAND	OSR_GLASS DOORS	OSR_ENTER	OSR_SOLID	OSR_SOLID_RC2	OSR_ATHOS	OSR_FORCA
symbol width.	А	D	Е		Ö					
"60"	600	690	719	•	•					
"70"	700	790	819	•	•	•				
"80"	800	890	919	•	•	•	•	•	•	•
"90"	900	990	1019	•	•	•	•	•	•	•
"90E"	904	994	1023	•		•	•	•		
"90E"	915	1005	1034						•	•
"100"	1000	1090	1119	•		•	•	•	•	•
"110"	1100	1190	1219	•		•			•	

**** - investment dimension "90E" different for technical and remaining doors

OSR STAND dimensions for double leaf door

TOT GOODIE TEAT GOOTS								
symbol width.	Α	D	E	F				
"100d"	1032	1122	1151	1151				
"110 _D "	1132	1222	1251	1251				
"120"	1232	1322	1351	1351				
"130"	1332	1422	1451	1451				
"140"	1432	1522	1551	1551				
"150"	1532	1622	1651	1651				
"160"	1632	1722	1751	1751				
"170"	1732	1822	1851	1851				
"180"	1832	1922	1951	1951				
"190"	1932	2022	2051	2051				
"200"	2032	2122	2151	2151				

type of the door frame	НО	HŚ	hw	hm	W
OSR_STAND					
OSR_ENTER	2072	2027 5*	2088	2007	30
OSR_SOLID	20/3	2027,5*	2088	2087	30
OSR_SOLID_RC2					
OSR_GLASS DOORS	2079	2033,5	2094	2093	30
OSR_ATHOS	2072	2027 5*	0000	2007	
OSR_FORCA	20/3	2027,5*	2088	2087	38
OSR OLIMP EI30	2073	2027,5	2088	2087	
steel adjustable door frame OSR OLIMP EI60	2072	2023	2083,5	2086	48


H0 - height of the wall opening

Hś - height of the door frame passage

^{***} applies to steel adjustable door frame OSR Olimp EI 60


 $^{^{}st}$ - with the use of a steel threshold - the actual height of the door frame passage will be reduced by 20mm from the floor

ADJUSTABLE METAL DOOR FRAME




ADJUSTABLE METAL DOOR FRAMES


Adjustable steel non-rebated door frames - dimensions



Vertical section of the OSRB




OSRB horizontal cross-section



D - width of the assembly hole

adjustable steel non-rebated door frame profile



Dimensions for single leaf doors

symbol width.	Α	D	E
"60"	624	714	743
"70"	724	814	843
"80"	824	914	943
"90"	924	1014	1043
"100"	1024	1114	1143

Dimensions for double leaf doors

symbol width.	А	D	Е
"120"	1271	1361	1390
"130"	1371	1461	1490
"140"	1471	1561	1590
"150"	1571	1661	1690
"160"	1671	1761	1790
"170"	1771	1861	1890
"180"	1871	1961	1990

Note: Extra charge for reinforcement for the door self closer ,

 $^{^{***}}$ - steel adjustable non-rebated OSRB STAND single-leaf door frames with 3 hinges, extra charge , for double-leaf doors with 6 hinges, extra charge of

HYBRID STEEL DOOR FRAMES

CONSTRUCTION:

Steel hybrid door frames are a solution combining the solidity of a metal structure with additional functionality allowing for full construction of the wall opening using wood-based door frame elements finished with CPL laminate. The hybrid door frame is a combination of a fixed-width metal door frame, a wood-based panel available in 11 width variants and a masking architrave. This solution allows for full construction of the wall opening with a thickness of 137-337 mm (145-345 for technical doors and 155-355 for Olimp El60 doors) and adjustment with an architrave up to 20 mm.

Door frame profile dimensions and equipment depend on selected option - door leaf model.

APPLICATION / TYPES OF OSH DOOR FRAMES (HYBRID STEEL DOOR FRAMES)

OSH for rebated interior door leaf OSH_STAND OSHB_STAND OSH for non-rebated interior doors OSH_GLASS OSH For interior glass doors

OSH_ENTER OSH for the door Enter, Enter Akustik, Revos

OSH_SOLID OSH for Solid doors OSH_SOLID_RC2 OSH for Solid RC2 OSH_ATHOS OSH for the Athos door leaf OSH_FORCA OSH for Forca or Forca B door leaf OSH for Olimp EI-30 door leaf OSH_OLIMP EI 30 OSH_OLIMP EI 60 OSH for Olimp EI 60 doors

All frames are designed to be mounted on the finished floor.

STANDARD OPTIONS IN OSH STAND

- » sockets for 2 or 3 hinges
- » socket for latch plate of main lock

In the door frame for double leaf doors - sockets for 4 or 6 hinges

STANDARD OPTIONS IN OSHB STAND

- » sockets for 2 or 4 hinges
- » magnetic lock latch

STANDARD OPTIONS IN OSH GLASS

- » sockets for 2 hinges
- » socket for latch plate of main lock

STANDARD OPTIONS IN OSH ENTER

- » sockets for 3 hinges
- » socket for main lock or additionally for upper lock

STANDARD OPTIONS IN OSH SOLID

- » sockets for 3 hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch bolts of multi-point lock used in SOLID model

STANDARD OPTIONS IN OSH SOLID RC2

- » sockets for 3 triple hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch bolts of multi-point lock used in SOLID model

STANDARD OPTIONS IN OSH ATHOS, FORCA

- » sockets for 3 triple hinges
- » additional sockets for anti-thrust bolts
- » sockets for latch plates of five point mortise lock (FORCA, FORCA B)
- » socket for latch plate of main lock (ATHOS)

STANDARD OPTIONS FOR OSH OLIMP EI30

RAL 7047

- » socket for latch plate of main lock
- » sockets for 3 triple hinges

AVAILABLE COLOURS

RAL 9003

Door frame is powder coated in two gloss scale (matt / low structure or semigloss / plain). There are available colours:

RAL 7024



AS A STANDARD STEEL HYBRID DOOR FRAME OSH **OLIMP EI60**

» socket for latch plate of main lock

RAL 7024

» sockets for 3 pcs. of three-part or object hinges



RAL 9003

RAL 7047

Adjustable panel with a masking architrave coated with CPL laminate from the list below:

RAL 8017

beige colour is available only in semi-gloss


RAL 1001

RAL 8017



HYBRID STEEL DOOR FRAMES

Hybrid steel rebated door frames - dimensions




type of the door frame.	НО	HŚ	hm	НС		
OSH_STAND						
OSH ENTER	2083	2027.5*	2092.5	2124		
OSH_SOLID	2083	2027,5	2092,5	2124		
OSH SOLID RC2						
OSH glass doors	2089	2033,5	2098,5	2130		
OSH_ATHOS	2005	0000 5*	20045	0407		
OSH FORCA	2085	2029,5*	2094,5	2126		
OSH OLIMP EI30	2081	2025,5	2090	2122		
OSH OLIMP EI60	2082	2023	2091,5	2119		
HO - height of the wall opening						

Hś - height of the door frame passage

- when using a steel threshold - actual

the height of the clear passage will decrease by 20mm

from the given one



Dimensions of the door fra	me
width	


Dimens width	OSH_STAND	OSH glass doors	OSHENTER	OSH_SOLID	OSH SOLID RC2	OSH_ATHOS	OSH FORCA				
symbol width.	А	D	Е	F							
"60"	600	710	730	792	•	•					
"70"	700	810	830	892	•	•	•				
"80"	800	910	930	992	•	•	•	•	•	•	•
"90"	900	1010	1030	1092	•	•	•	•	•	•	•
"90E"	904	1014	1034	1096	•		•	•	•		
"90E"	915	1025	1045	1107						•	•
"100"	1000	1110	1130	1192	•		•	•	•	•	•
"110"	1100	1210	1230	1292	•		•			•	

^{**** -} investment dimension "90E" different for technical and remaining doors

D - width of the assembly hole

Select the appropriate option of the adjustable panel with masking architrave (Cmin) for a specific wall thickness

door frame profile



		-					
		wall thickn	ess range	9			
OSH_ATHOS OSHFORCA OSH for Olimp EI-30 door leaf		OSH STAND OSH GLASS OSH ENTER OSH SOLID OSH SOLID RC2		OSH OLIMP EI60		SP	
option Cmin	Max	option Cmin	Max	option Cmin	Max		
145	165	137	157	155	175	82	
165	185	157	177	175	195	102	
185	205	177	197	195	215	122	
205	225	197	217	215	235	142	
225	245	217	237	235	255	162	
245	265	237	257	255	275	182	
265	285	257	277	275	295	202	
285	305	277	297	295	315	222	
305	325	297	317	315	335	242	
325	345	317	337	335	355	262	
345	365	337	357	355	375	282	

Price for double-leaf doors: + 30%

OSH OLIMP EI30 dimensions

for single leaf door

symbol width.	А	D	Е	F
"80"	802	912	932	994
"90"	902	1012	1032	1094
"90E"	917	1027	1047	1109
"100"	1002	1112	1132	1194
"110"	1102	1212	1232	1294

Dimensions OSH OLIMP EI60

TOT SITISTE TEAT GOOD								
symbol width.	А	D	Е	F				
"80"	797	907	934	989				
"90"	897	1007	1034	1089				
"90E"	926	1036	1063	1118				
"100"	997	1107	1134	1189				
"110"	1097	1207	1234	1289				

OSH STAND dimensions for double leaf doors

symbol width.	Α	D	E	F
"100d"	1032	1142	1162	1224
"110 _D "	1132	1242	1262	1324
"120"	1232	1342	1362	1424
"130"	1332	1442	1462	1524
"140"	1432	1542	1562	1624
"150"	1532	1642	1662	1724
"160"	1632	1742	1762	1824
"170"	1732	1842	1862	1924
"180"	1832	1942	1962	2024
"190"	1932	2042	2062	2124
"200"	2032	2142	2162	2224

Door Frame price = price of the metal part + price of an adjustable panel with a architrave

Prices for the adjustable panel with masking architrave


^{** -} dimensions for remaining OSH frames


 $^{^{\}ast\ast\ast}$ - dimensions for OSH ATHOS, OSH FORCA and OSH OLIMP EI 30

^{***** -} dimensions for OSH OLIMP EI 60

HYBRID STEEL DOOR FRAMES


Steel Hybrid non-rebated door frames - dimensions





OSHB horizontal cross-section X-X F wall A D E

hybrid steel non-rebated door frame profile



D - width of the assembly hole

Select the appropriate option of the adjustable panel with masking architrave (Cmin) for a specific wall thickness

Dimensions for single leaf doors

symbol width.	Α	D	Е	F
"60"	624	734	754	816
"70"	724	834	854	916
"80"	824	934	954	1016
"90"	924	1034	1054	1116
"100"	1024	1134	1154	1216

Dimensions for double leaf doors

symbol width.	Α	D	Е	F		
"120"	1271	1381	1401	1463		
"130"	1371	1481	1501	1563		
"140"	1471	1581	1601	1663		
"150"	1571	1681	1701	1763		
"160"	1671	1781	1801	1863		
"170"	1771	1881	1901	1963		
"180"	1871	1981	2001	2063		


SMALL ANGULAR STEEL DOOR FRAMES


CONSTRUCTION:

Steel door frames are made of 1.2 mm thick low-carbon steel sheet, protected with a protective organic varnish coating. The door frame consists of two beams: a hook and a hinged one, and a lintel, permanently connected together by welding. Hinged beams are equipped with hinge sockets (2-3 pcs.), while catch beams have cutouts for the tongue and latches for the lock of a dedicated door leaf (the set includes a cover seal).


APPLICATION

Small Angular Steel Door Frame - door frame designed for rebated interior doors










Dimensions for single leaf doors

symbol width.	A	С	D	E
"60"	600	633	690	710
"70"	700	733	790	810
"80"	800	833	890	910
"90"	900	933	990	1010
"90E"	904	937	994	1014
"100"	1000	1033	1090	1110



AVAILABLE COLOURS

Door frame is powder coated in two gloss scale (matt / low structure or semi-gloss / plain). There are available colours:













DARK GRAY semi-gloss RAL 7024



black matt

RAL 9005



semi-gloss beige *** RAL 1001

*** beige colour is available only in semi-gloss



POLARIS door handle - chrome inserts in DRE-Cell, 3D and CPL colors



simple key backplate



cylinder lock backplate



toilet lock backplate



POLARIS door handle - black matt inserts in DRE-Cell, 3D and CPL colors



simple key backplate



cylinder lock backplate



toilet lock backplate



WEGA door handle - satin nickel



simple key backplate



cylinder lock backplate



toilet lock backplate



WEGA door handle - black matt



simple key backplate



cylinder lock backplate



toilet lock backplate



ATRIA door handle - satin nickel



simple key backplate



cylinder lock backplate



toilet lock backplate



ATRIA door handle - black matt



simple key backplate



cylinder lock backplate



toilet lock backplate



ORION door handle - satin nickel



simple key backplate



cylinder lock backplate



toilet lock backplate



ORION door handle - black matt



simple key backplate



cylinder lock backplate



toilet lock backplate



ARCTUS door handle - satin nickel



simple key backplate



cylinder lock backplate



toilet lock backplate



door handle MEDA - shiny chrome inserts in DRE-Cell, 3D and CPL colours



simple key backplate



cylinder lock backplate



toilet lock backplate



QUBIK door handle - black with antibacterial coating *



simple key backplate



cylinder lock backplate



toilet lock backplate*



CUBE SLIM door handle - brushed chrome



simple key backplate



cylinder lock backplate



toilet lock backplate



the CUBE SLIM handle - shiny brass



simple key backplate



cylinder lock backplate



toilet lock backplate



TOTAL door handle - brushed nickel matt



simple key backplate



cylinder lock backplate



toilet lock backplate

^{* -} the handle and the toilet knobs are covered with an antibacterial coating



IBIZA door handle - black matt



CUBE door handle - shiny chrome



CUBE door handle - brushed nickel



simple key



simple key backplate

simple key backplate

simple key backplate

cylinder lock

backplate

cylinder lock backplate

cylinder lock

backplate

backplate



cylinder lock

backplate

cylinder lock backplate



toilet lock

backplate

toilet lock backplate

toilet lock

backplate

toilet lock backplate



MONDO door handle - satin nickel

CUBE door handle - black matt



door handle TREND - satin nickel



simple key backplate

simple key backplate



cylinder lock backplate



toilet lock

toilet lock backplate



door handle LINEA - shiny chrome



LINEA door handle - nickel satin



simple key backplate

simple key

backplate



, backplate



cylinder lock backplate



toilet lock backplate



toilet lock backplate



QUANTA Fit door handle - brushed brass



door handle BELLA SLIM - glossy brass



door handle ZORBA - shiny chrome/satin



QUIK Fit door handle - black



door handle NOVA - stainless steel



PROXIMA door handle - stainless steel



TOPAZ door handle - stainless steel



TOPAZ door handle - stainless steel, black matt



simple key backplate



simple key backplate



simple key backplate



simple key backplate



simple key backplate



simple key backplate



simple key backplate



simple key backplate



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



toilet lock backplate



toilet lock backplate



toilet lock backplate



toilet lock backplate



toilet lock backplate



toilet lock backplate



toilet lock backplate



toilet lock backplate



handle JOWISZ - stainless steel



LUNA SLIM door handle - brushed chrome



LUNA slim door handle - shiny brass



IBIZA door handle - graphite/chrome



door handle IBIZA - nickel satin



door handle IBIZA - shiny chrome



handle BETA - nickel satin



EUROPA door handle - nickel satin



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



TOMA door handle - black



STARK Fit door handle - black



WARNA door handle - satin nickel



door handle ALVA LUX - black matt



PEM LUX door handle - black matt



AS LUX door handle - titanium



LEA LUX door handle - gold matt



FOKUS door handle - nickel satin velvet



simple key backplate







toilet lock backplate



simple key backplate



cylinder lock backplate





toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



cylinder lock backplate



toilet lock backplate



simple key backplate

simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



simple key backplate



cylinder lock backplate



toilet lock backplate



UNO door handle - stainless steel



ROMAN door handle - chrome/nickel lacquered



TIK-QR door handle - anthracite



QUBIK door handle - lacquered nickel



LIBRA door handle - satin nickel





ZORBA door handle with oblong backplate long backplate - shiny chrome /



simple key backplate



simple key backplate



simple key backplate



simple key backplate



Simple key backplate



ZORBA door handle with a long simple key backplate - shiny chrome/satin (spacing 72 mm)



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



cylinder lock backplate



ZORBA door handle with oblong backplate for cylinder lock - shiny chrome/ satin (span 72 mm)





toilet lock backplate



toilet lock backplate



toilet lock backplate



toilet lock backplate



ZORBA door handle with oblong backplate long bathroom backplate - shiny chrome / satin (spacing 72 mm)



door handle SHARK black and inox door handle SZARK for the SOLID /





door handle DIVA and backplate for door leaves FORCA 10 and FORCA B 10 silver F1 door handle long backplate



ONTARIO door handle and backplate for SOLID RC2 model silver colour F1 door handle long backplate



STAR TEC technical handle - class IV stainless steel matt price for a set (handle + cylinder lock backplate)

door leaf thickness up to 55 mm

exterior backplate



cylinder lock , backplate




PEGAZ door handle (span 72 mm) black matt with cylinder lock



door handle TOM with oblong backplate for cylinder lock (span 72 mm) matt chrome



handle METRO (span 72 mm) stainless steel for cylinder lock



upper backpate METRO stainless steel for cylinder lock



exterior TOTAL door handle with long short upper backplate TOTAL backplate (72 mm span) inox plus -

short inox plus

Note: long backplates do not fit doors with magnetic lock

CYLINDER LOCK INSERTS



insert 26/41 - nickel matt



insert 26/41 - satin brass



set of cylinder lock inserts ZN 30/40+30G/40 SN or ZN 30/40+40G/30 SN satin nickel



one key system

set of cylinder lock inserts ZN 30/40+30G/40 SB or ZN 30/40+40G/30 SB brass satin



set of inserts ZN 27/40+27G/40 or ZN 27/40+40G/27 satin nickel



insert 30/30 - satin nickel



insert 35/35 - satin nickel



insert 30/40 - satin

SELFCLOSER






DORMATS-71 selfcloser Price.....



GEZE TS 2000 selfcloser



DECORS


















DECORS



white

bleached craft oak


gold craft oak

shirin walnut

DRE-PRINT collection G




Scaling of the patterns in G1 - G6 graphics in the sleceted door leaves widths right opening



Scaling of graphics patterns in the width of the door leaf "80" is presented on page 54 and 55 $\,$



Scaling of the patterns in G7 - G12 graphics in the sleceted door leaves widths right opening



Scaling of graphics patterns in the width of the door leaf "80" is presented on page 54 and 55

DRE-PRINT collection G



Scaling of the patterns in G13 - G18 graphics in the sleceted door leaves widths right opening




Scaling of graphics patterns in the width of the door leaf "80" is presented on page 54 and 55 * pattern versions available for the right and left door leaf




Scaling of the patterns in G19 - G25 graphics in the sleceted door leaves widths right opening

G19 graphic pattern G20* graphic pattern G21 graphic pattern G22 graphic pattern G24* graphic pattern G24* graphic pattern G25 graphic pattern G25 graphic pattern G26* graphic pattern G26* graphic pattern G27* graphic pattern G28* graphic p



Scaling of graphics patterns in the width of the door leaf "80" is presented on page 54 and 55* pattern versions available for the right and left door leaf

GLASS PANE PATTERNS



GLASS PANE PATTERNS





white frost laminated VSG 22.1, plain on both sides



window blind



white bark



decormat graphite



decormat brown



chinchila




VSG black


Prices and availability of glass are given on the pages with door leaves. The glass in the doors of our collections has an obverse and a reverse (except VSG 22.1 and VETRO E, VETRO D1).

ARCHITRAVES AND SKIRTING BOARDS

KT2 ARCHITRAVE


The KT2 80 mm and 63 mm architrave increases the adjustment range of the standard adjustable OR door frame by +15 mm. The architrave must be ordered separately as a separate accessory. The price of the architrave is available at the Distributor.







ARCHITRAVES





application: fixed door frame, fixed door frame SOFT

Set contains (for one side of the door):

horizontal and two vertical masking architraves, plastic latch strike plates, pins and clamp clips. Masking architraves are packed in a cardboard box.

TOP*

OUARTER ROUNDS

The quarter round is used to mask the angular connection of the wall and the door frame. The trading unit is $1\ \rm pc.$ prices of quarter rounds

Quarter rounds require cutting before the assembly.



quarter round $16 \times 16 \times 2200 \text{ mm}$




P R P R P R

quarter round SOFT 11 × 18 × 2200 mm

SKIRTING BOARDS



Length of skirting boards 2.62 meters (except for LPP4W). Skirting boards require cutting before assembly.



Lenght of LPP4W is 2,40 mb It is made of moisture resistant board.

VENTILATION GRILLE

There is possibility to instal bathroom plastic ventilation grille, which is available in the following colours: white, beige, calvados, brown, silver, creamy, gray, black and ashen (except for frame construction doors, sliding doors, fire resistant doors and SOLID, ENTER) or aluminum ventilation grille

- » plastic ventilation grille
- » aluminum ventilation grille



plastic ventilation grille



aluminum ventilation grille

VENTILATION ACCESSORIES AND OTHER

VENTILATION SLEEVES FOR PANEL DOORS

There is possibility to purchase a set (5 pcs) of ventilation sleeves. DRE-Cell Decor, 3D foil, CPL laminate.



VENTILATION SLEEVES FOR FRAME CONSTRUCTION DOOR LEAF

For frame construction doors, except for VETRO with plastic sleeves (3 sleeves for doors "60", 4 sleeves for doors "70", 5 sleeves for doors "80"-"100")

PLASTIC VENTILATION SLEEVES



VENTILATION UNDERCUT

In all collections (except SOLID, SOLID RC2, ENTER, FIRE resistant door leaves, sliding doors, folding), ventilation undercut can be made upon request.



13.5 MM HINGE FOR REBATED DOORS

- » (set of lower and upper part)
- 13.5 mm diameter hinge in black.



HINGE COVERS


» (set of 2 pcs. for 1 hinge) Plastic hinge covers are adjusted to hinges with diameter of 13.5 mm.



thimble



DOOR LEAF DIMENSION AND PLACEMENT OF HINGES



DOOR LEAF WIDTH

Symbol of the door dimension	S	SW	SWSE	SWS
"60"	644	618	620	-
"70"	744	718	720	-
"80"	844	818	820	824
"90"	944	918	920	924
"100"	1044	1018	1020	1024
"110*"	1144	1118	-	-

S - total door leaf width SW - width in the rebate (refers to rebated door leaf) SWSE - Sara Eco 2 leaf width SWS - width in the rebate of folding door leaf - width "110" is only available in

NOTE: Total width of "40" side panels is 444 mm.

door leaves Standard 10, Athos, **Enter Acoustic and Olimp**

ADDITIONAL LEAF WIDTHS

Symbol of the door dimension	S	SW
"90E" for OLIMP EI30, ATHOS, FORCA, FORCA B.	959	933
"90E" for OLIMP EI60	973	947
"90E" for STANDARD, ENTER, ENTER AKUSTIK, SOLID, SOLID RC2	948	922

The investment standard "90E" provides 900mm passage in the door frame with the door leaf opened at an angle of 90 $^{\circ}$

DIMENSIONS OF THE DOOR LEAF WITH 4 VARIABLE HEIGHTS

(refers to door leaf STANDARD 10 and collections MODERN and PLUS)

Н	H1	НК	HZ	HZ2	HZ3
1983	1970	850	1672	606	1653
2043	2030	910	1732	626	1713
2110	2097	977	1799	647	1780
2240	2227	1107	1929	691	1910

H - total height of the door leaf

H1 - door leaf height in the rebate

HK - distance form the top rebate of door leaf to the axis of the handle

HZ - distance from the upper edge of the door leaf to the mounting point of the third hinge

DOOR LEAF HEIGHT

2043 mm - total height of rebated and non-rebated door leaf (2010 for folding doors)

2030 mm - height of the rebated door leaves in the rebate (2020 for Sara Eco 2 door leaves with the inverted rebate, 2000 for folded doors)

2055 mm - total height of the door leaves with inverted rebate

1983, 2043, 2110, 2240 mm - total possible height of STANDARD 10 door leaf and MODERN and PLUS collection (1970, 2030, 2097, 2227 mm - measured in the door leaf rebate)

SHORTENING OF DOOR LEAF

There is possibility to shorten the door leaf on your own, up to 60 mm (there is no possibility to shorten following door leaf: VETRO, FIRE RESISTANT DOORS, FORCA B, door leaf of all collections in the sliding version, passive doors, glass doors, folding doors and door leaves with dropping seal).

Note: The door leaf with recuperative undercutting - 15 mm, is adapted to shortening on your own, up to 45 mm Max.

CLEARANCE BETWEEN DOOR LEAF AND FLOOR

tandard clearance between door leaf and finished floor is 8 mm high (15 mm in FOLDE door leaf, 5-6 mm in OLIMP door leaf).

NOTES REFERED TO HINGE

In rebated door leaves: frame construction door leaves, entrance doro leaves (Enter, Enter Akustik, Solid) and other collections with a width of not less than "90", 3 pcs. of screw-in hinges ø 13.5 mm are installed. In other rebated interior doors, it is possible to choose 2 or 3 hinges.

In SOLID RC2, FORCA, FORCA B, ATHOS and OLIMP EI30 door leaf there are mounted 3 threefold hinges.

The OLIMP EI60 leaves, depending on the width, are equipped with 3 three-part hinges or 3 SIMONSWERK hinges VX 7939/160. Non-rebated door leaf come with pre-milled sockets for two or three hidden concealled hinges which are attached together with nonrebated door frame.

Sara Eco 2 door leaves with inverted rebate and non-rebated doors have milled sockets for recessed hinges, which are packed together

Folding doors come with 3 hidden recessed hinges which join two parts of door leaf.

Door leaves with inverted rebate have sockets for two concealled hinges, which are packed together with door frame.

Non-rebated door leaf



edge without rebate



lock magnetic



hinge recessed hinge

REBATED DOOR LEAF



fixed edge



threefold hinge



threefold hinge



SIMONSWERK VX 7939/160 hinge

DOOR LEAF THICKNESS AND SELECTION OF CYLINDER INSERT

Door leaf type	Door leaf	proportion	reccommended**	Refers to cylinder ins	ert with door knob
	thickness i	in the door leaf (W0/Z0)	dimension of the cylinder insert (W/Z)	Cylinder insert with a knob on the inside (W/Z)	Cylinder Insert with a door knob outside (W/Z)
rebated door leaf	40	14 / 26	25 / 40 ; 26 / 36 26 / 41 ; 30 / 40	25G/40; 26G/36 26G/41; 30G/40 27G/40	25/40G; 26/36G 26/41G; 30/40G 27/40G
Sara Eco 2 inverted rebate door leaves	40	24 / 16	35 / 30 ; 36 / 26 36 / 31 ; 40 / 30	35G/30; 36G/26 36G/31; 40G/30	35/30G; 36/26G 36/31G; 40/30G
Non-rebated door leaf	40	20 / 20	31 / 31 ; 30 / 30 35 / 35	31G/31; 30G/30 35G / 35	
Profi non-rebated door leaves	50	25/25	35/35; 36/36 40/40; 41/41	35G/35 ; 36G/36 41G/41 ; 40G/40	
Non-rebated door leaf Sara Eco 2	40	16 / 24	30 / 35 ; 26 / 36 31 / 36 ; 30 / 40	30G/35; 26G/36 31G/36; 30G/40	30/35G; 26/36G 31/36G; 30/40G
Door leaf with inverted rebate	40	27 / 13	40 / 25 ; 41 / 26	40G/25; 41G/26	40/25G; 41/26G
Profi Door leaf with inverted rebate	50	30/20	40/30; 41/31 45/35	40G/30 ; 41G/31 45G/35	40/30G ; 41/31G 45/35G
Folding doors	40	17/23	30/35; 31/36 30/40	30G/35; 31G/36 30G / 40	30/35G; 31/36G 30 / 40G
fire resistant. ATHOS	50	21 / 29	31 / 41 ; 35 / 40	31G/41; 35G/40	31/41G; 35/40G
Olimp El30	50	18 / 32	30 / 45 ; 31 / 46	30G/45; 31G/46	30/45G; 31/46G
Olimp EI60	60	28 / 32	40 / 45 ; 41 / 46	40G/45; 41G/46	40/45G; 41 / 46G
fire resistant. FORCA	50	22 / 28	35 / 40		
SOLID RC2	40,6	14 / 26,6	26 / 40 ; 26 / 41 30 / 40		

Cylinder inserts are reversible - that is 25/40 = 40/25, 26G/36 = 36/26G

fig. selection of cylinder insert dimension





fig. selection of cylinder insert dimension with door knob



Dimension of cylinder insert is calculated using the following formula:

WO + backplate thickness + 2÷3mm / Z0 + backplate thickness + 2÷3mm

where:

WO and ZO - values have been presented in the table above thickness of the backplate - measured (presented values in above table assume that backplate is 10mm thick)


Selection of backplate with door knob - if we want to mount a knob on:

- the inner side of door leaf symbol of the door knob must be next to "W" dimension (see column 5 in the table)
- the external side of the leaf symbol of the door knob must be next to "Z" dimension (see column 6 in the table)


^{**}reccommended dimensions (assuming that backplate is 10 mm thick, and patented cylinder doesnt exceed 5 mm above backplate).

SINGLE LEAF REBATED DOOR

We offer left, right and central door leaf



hinges are located on right side when viewing from hinges sight



hinges are located on left side when viewing from hinges sight

centra door leaf

without locks and hinges

DOUBLE LEAF REBATED DOOR


We offer double leaf doors: the right - then right door leaf becomes an active one and left door leaf becomes inactive, and double left leaf - left leaf is an active one and the right one is inactive.


The active door leaf has a rebate and a lock as a standard. For double-leaf doors, the edge on the side where the active leaf lock is located and the passive leaf on the side where the catch is located is always a straight edge.

Inactive door leaf comes with a "counter rebate" and additionally is equiped with a latch strike plate and a flush bolt as a standard fitting (A)



flush bolt (A)






Only door frames produced by DRE fit double-leaf doors, that is the reason that we reccomend to our customers to buy doors as a complementary sets. Whole DRE set comprises of 2 door leaf and door frame.



Symbol	dimension in [mm]					
of door dimension	S2	S2W	combination* Sc+Sb			
"100d"	1078	1052	644+444			
"110d"	1178	1152	744+444			
"120"	1278	1252	844+444; 644+644			
"130"	1378	1352	944+444; 744+644; 644+744			
"140"	1478	1452	1044+444; 844+644; 744+744; 644+844			
"150"	1578	1552	944+644; 844+744; 744+844; 644+944			
"160"	1678	1652	1044+644; 944+744; 844+844;			
			744+944; 644+1044			
"170"	1778	1752	1044+744; 944+844; 844+944; 744+1044			
"180"	1878	1852	1044+844; 944+944; 844+1044			
"190"	1978	1952	1044+944; 944+1044			
"200"	2078	2052	1044+1044			
combination* possible combination of active (Sc) and inactive (Sb) leaf width						

NON-REBATED DOOR LEAF - SLIDING VERSION


We offer left, right and central door leaf (door leaf without a lock and handle)



when active leaf is equipped with lock non-active leaf is equipped with latch strike plate

SINGLE LEAF DOOR NON-REBATED

We offer left, right and central door leaf




when viewing from the side of the room (door leaf unit is opened towards opening direction)

DOUBLE LEAF NON-REBATED DOOR

We offer double leaf doors: the right - then right door leaf becomes an active one and left door leaf becomes inactive, and double left leaf - left leaf is an active one and the right one is inactive.

An active door leaf hos lock as a standard option. Inactive door leaf is equiped with a latch strike plate and a flush bolt as a standard fitting.



 $^{^{\}ast}$ for double lef non-rebated doors there is possibility to purchase cover stripe width of cover stripe 30 mm



Symbol of door	dimension in [mm]				
dimension	S2	combination* Sc+Sb			
"120"	1291	644+644			
"130"	1391	744+644; 644+744			
"140"	1491	844+644; 744+744; 644+844			
"150"	1591	944+644; 844+744; 744+844; 644+944			
"160"	1691	1044+644; 944+744; 844+844;			
		744+944; 644+1044			
"170"	1791	1044+744; 944+844; 844+944; 744+1044			
"180"	1891	1044+844; 944+944; 844+1044			
combination* - p	ossible co	mbination of active (Sc) and inactive (Sb) leaf			

combination* - possible combination of active (Sc) and inactive (Sb) leawidth

CONSTRUCTION OF PANEL DOORS

- » door leaf frame made of coniferous wood or MDF
- » Core: stabilizing insert "honeycomb" (A), perforated chipboard (B) and in fire proof doors: chipboard
- » External 3mm HDF board or external HDF 4mm board (in Finea, Finea B, Enter, Enter Acouustic, Solid)
- » type of edge straight or without rebate


External boards of door leaf is finished with:

a) in DRE-Cell Decor collection - decorative foil based on the polypropylene


b) in 3D foil - 3D foil based on decorative paper

c) in CPL laminate - CPL laminate th. 0.15-0.2mm or 0.7 mm


Fire resistant door leaf Olimp El30




Fire resistant door leaf Olimp EI60




Anti-burglary door and fire-resistant door leaf Forca EI30



Anti-burglary door leaf Forca B




Anti-burglary door leaf SOLID RC2



sandwich type construction 2XHDF divided 0,3 mm alu foil

Fire-resistant door leaf Forca EI30





(A) stabilising insert "honeycomb"




(B) perforated chipboard

FRAME CONSTRUCTION DOORS (IS NOT REFFERED TO VETRO A,B,C,D,F)


Frame construction door leaf is entirely made of wood-based panels: vertical stiles made of wood-based panels - 40 mm external horizontal stiles made of wood-based panels - 35 mm horizontal rails (interior):

- wood-based boards - 22 mm in Lumio, Vico, Auri, Piano, Even, Premium, Fosca, Verso, Reva, Solte, Triesta*, Ena*, Verano* door leaves (* In Ena 1-2, Triesta 1-2 collection, 1-2, Verano 1-2, the frame next to the large glass pane is made of wood-based boards - 35 mm. However, in Ena 3-5, Verano 3-5, 3-5 and Triesta 3 models, there are two stiles next to the large glass panes made of wood-based boards - 35 mm.) - wood-based panels - 35 mm in Nestor, Elsa, Scala, Berge, Estra door leaves.


Horizontal cross-section of door leaf Lumio, Vico, Auri, Verano, Piano, Premium, Fosca, Verso, Ena, Even, Triesta, Reva, Solte




Horizontal cross-section of ELSA




Horizontal cross-section of Ena, Verano and Trieste doors (cross-section at the height of the rail and stile set by the large glass pane)



Horizontal cross-section of Nestor



Horizontal cross section of the door leaf Scala, Berge



FILLINGS OF FRAME CONSTRUCTION DOOR LEAF:

Scala A; - 4 mm glass pane, flat 4 mm HDF board

Scala B - 4 mm glass pane, 19 mm MDF profiled board

Elsa A - 4 mm glass pane, flat 4 mm HDF board

Elsa B - 4 mm glass pane, 19 mm MDF profiled board

Premium 1-3 - 4 mm glass pane

Premium 4-7, 12 - 4 mm glass pane, 4 mm HDF marquetries made in door leaf colour Premium 8-11, 13 - 4 mm glass pane, 4 mm HDF marquetries coated with silver laminate

Piano 1-6 - 4 mm glass pane, 16 mm MDF profiled board

Piano 9-12 - 4 mm glass pane, 19 mm MDF profiled board

Fosca 1-3 - 4 mm glass pane, 4 mm HDF board coated with silver laminate


Fosca 4-6 - 4 mm HDF board coated with veneer in door leaf colour

Nestor, Berge - 4 mm glass, 19 mm profiled MDF panel


Ena, Trieste, Auri, Verano, Even, Reva, Solte, Verso - 4 mm glass pane

Estra - 4 mm glass, 16 mm flat MDF panel, undercuted

profile of 19 mm MDF board (Scala B, Piano 9-12, Elsa B, Nestor, Berge)



profile of 16 mm MDF (Piano 1, 2, 5, 6)



KICK PLATES

Kick plates so called "OKOPNIK!" it is finishing solution for selected panel door models with straight edge.

We offer door leaves covered with stainless steel sheets of thickness. 0.6 mm in the form of bottom or middle panels. It is also possible to have both panels in the selected door leaf at the same time. The height of the panels is 300 mm.

Door leaf with kick plates must be filled with perforated chipboard.







door leaf model with middle panel



door leaf model with bottom and middle panel

There is possibility to order door leaf with bottom panel and ventilation undercut.

NOTE: If you wish to place an order, please contact the Customer Service Department.

REMAINING TECHNICAL INFORMATIONS:

1. While maintaining the standard dimensions of door leaves and door frames, the gap between the "ready" floor and the lower edge of the door leaf is 8 mm. In order to reduce the above gap, the door frame should be shortened appropriately from the bottom (does not apply to FOLDE and OLIMP).

2. NOTE! Before purchasing and installing construction joinery, check whether the selected type of joinery complies with the requirements of the technical design developed for a given project, and in particular, make sure whether the structure of the walls and ceilings allows the installation of construction joinery with the weight specified in the table below:

	door leaf			Door fra	mes	other p	roducts
	interior	entrance	fire-resistance	adjustable	fixed	Adjustable tunnel	Sliding system
Max weight	50 kg*	50 kg*	105 kg*	40 kg	20 kg	40 kg	20 kg

^{*} max weight of single leaf door

- 3. Door leaf is wrapped in shrink film and the edges are additionally protected with Styrofoam or cardboard inserts.
- 4. Price of door leaf does not include door handles, backplates and cylinders insert (with the exception of SCALA A and B collections in rebated and non-rebated versions in DRE-Cell veneer and 3D veneer also excluding NESTOR and ELSA collections in rebated and non-rebated version in DRE-Cell veneer and 3D veneer, where handle and backplate come).
- 5. It is possible to purchase CENTRA doors and door frames (without drilling for locks and hinges option not available for fire resistant doors, ENTER/SOLID, ENTER AKUSTIK, SOLID RC2, FORCA B, Sara Eco 2, FOLDE) for the price of a similar product with fittings and drilling. CENTRA door frames have seals. The set does not include fittings.

CROSS-SECTIONS OF ALUMINUM FRAMES

DRE profile for nonrebated outward opening doors



DRE profile for doors with inverted rebate opened inwards



Profile for nonrebated outward opening doors



Profile for doors with inverted rebate opened inwards




6. In accordance with applicable regulations, doors to the bathroom, washroom and a separate toilet should open to the outside of the room, and be at least 0.8 m wide and 2 m high, and have openings in the lower part with a total cross-section of not less than 0.022^{m2} for air supply. The ventilation area of the door is the sum of the areas of available ventilation elements: ventilation grille (ensures a ventilation area of 0.022 m^2 in all door widths) or ventilation undercut or ventilation sleeves and the clearance area between the door leaf and the floor.

Ensuring ventilation surface for rebated doors**

· · · · · ·						
Complete of		ventilation eves	doors with ventilation undercut			
Symbol of door leaf dimension	ventilation surface of sleeves and the clearance 8 mm [m2]	required clearance to meet ventilation requirements [in mm]	ventilation surface of the undercut and the clearance 8 mm [m2]	required clearance to meet ventilation requirements [in mm]		
"100"	0,011	19*	0,033	0		
"90"	0,010	21*	0,029	1		
"80"	0,009	24*	0,025	4		
"70"	0,008	28*	0,021	14*		
"60"	0,007	33*	0,018	35*		

Ensuring ventilation surface for Sara Eco 2 doors and all non-rebated doors

Listing ventilation surface for Sala Eco 2 doors and all non-repated do						
Symbol of door leaf dimension	doors with	ventilation eves	doors with ventilation undercut			
	ventilation surface of sleeves and the clearance 8 mm [m2]	required clearance to meet ventilation requirements [in mm]	ventilation surface of the undercut and the clearance 8 mm [m2]	required clearance to meet ventilation requirements [in mm]		
"100"	0,0112	19*	0,033	0		
"90"	0,0104	21*	0,029	1		
"80"	0,0096	23*	0,025	4		
"70"	0,0082	27*	0,021	12*		
"60"	0,0074	32*	0,018	31*		




The above - stated required clearance height of the space under the door assures total ventilation surface of 0.022 m2. The standard clearance for door leaf is 8mm high.

- * it is necessary to increase the clearance to the specified height by shortening door leaf at the bottom (when such a shortening is possible see**)
- ** Exceptions that are not included in the table (door leaf that can not be shortened):
- collection Vetro A , D and E the use of ventilation undercut in the door with a width of "80" "100" and a standard ground clearance of the door (8 mm) will fulfill ventilation requirements.
- Vetro B collection does not meet the ventilation requirements.
- sliding door leaf due to design of the sliding system (distance from the wall/tunnel about 12 mm), door leaf meet ventilation requirement without need for additional options.

there is no possibility to shorten double leaf doors and folding doors FOLDE.

VENTILATION UNDERCUT





GALLA 1 decormat - glass door sliding system

EXPLANATIONS:

- panel doors , DRE Cell decor
- frame construction doors, DRE Cell decor
- entrance doors, DRE Cell decor
- panel doors, 3D decor
- frame construction doors, 3D decor
- entrance doors, 3D decor
- panel doors, Finish foil
- panel doors, painted
- R frame construction doors, painted
- R laminated frame construction doors

- panel doors, CPL Laminate
- entrance doors, CPL Laminate
- technical doors, CPL Laminate
- s glass doors
- PROFI panel construction doors
- e panel doors Sara Eco 2
- smoke-proof technical doors
- fire resistant technical doors
- anti-burglary doors
- panel construction doors, lacquered
- panel construction doors, synchronous laminate
- R frame construction doors, synchronous laminate

Presented prices of the door leaves doesnt include prices of the door frames and door handles.

The price list is valid from March 1, 2024.

Producer provides 24 months of warranty for door leaf and door frames.

The photos and visualizations used in the catalog show door leaves with a width of 80 cm (does not apply to side pannels). In the case of other door leaf widths, the proportions of the collection pattern, glazing, frames, millings and graphics will change. More technical informations and informations refered to assembly process are available in product guarantee card.

The folder does not constitute an offer according to the law and is published for information purposes only. The above information is valid starting from the date of this publication. Pursuing a policy of continuous development, we reserve the right to make changes and improvements to the products presented in the folder without prior notice. The colors presented in the catalogue may differ from the actual ones. We reserve the right to make printing errors.

Technical approvals:

National Technical Assessment ITB-KOT-2019/0860 issue 1 (sliding system)

National Technical Assessment ITB-KOT-2018/0633 release 2 (FORCA, ATHOS fire doors)

National Technical Assessment ITB-KOT-2022/2051, edition 1 (glass door)

National Technical Assessment ITB-KOT-2021/1945 edition 1 (folding and sliding glass doors)

National Technical Assessment ITB-KOT-2017/0011 edition 2 (ENTER / SOLID / SOLID RC2)

National Technical Assessment ITB-KOT-2018/0407 edition 2 (OLIMP)

PN-EN 14351-2: 2018-E12 (interior doors)

National Technical Assessment ITB-KOT-2019/1132 edition 1 (SARA door leaf)

National Technical Assessment ITB-KOT-2019/0805 edition 1 (steel door frames)



r Day

I Day

DYSTRIBUTOR

DRE

82-300 Elblag - Gronowo Górne, ul. Nefrytowa 4 Headquarters: phone 55 236 42 58 Customer service department: phone 55 236 42 43 to 48 fax 55 236 42 51 Marketing department: phone 55 236 42 40 working hours: 8:00 - 16:00 e-mail: dre@dre.pl, eksport@dre.pl www.dre.pl